

# 1430 Protector

Top Loader Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli<sup>™</sup> Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

#### • Unique top loading design

- 3 level Pick N Pluck<sup>™</sup> with convoluted lid foam
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- · Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Stainless steel hardware and padlock protectors
- Optional shoulder strap available
- Peli's legendary lifetime guarantee\*\*
- \* Where applicable by law



## CONFIGURATIONS



1430 Standard



**1434** With Padded Dividers & Lid Organizer



**1437** With Padded Office Divider Set & Lid Organizer



**1430NF** No Foam



**1430WF** With Foam

### DIMENSIONS

Interior (L×W×D)	13.56 x 5.76" x 11.70 (34.4 x 14.6 x 29.7 cm)
Exterior (L×W×D)	16.40 x 8.71" x 13.15 (41.7 x 22.1 x 33.4 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	9.70" (24.6 cm)
Total Depth	11.7" (29.7 cm)
Int Volume	0.53 ft³ (0.015 m³)
Padlock Hole Diameter	0.31" (0.8 cm)

#### MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane

Purge BodyABSPurge Vent3 Micron Hydrophobic Non-Woven

#### COLOURS

Black

### WEIGHT

Weight With Foam	6.50 lbs (2.9 kg)
Weight Empty	5.60 lbs (2.5 kg)
Buoyancy	59.00 lbs (26.8 kg)
Master Pack Weight	8.09 lbs (3.7 kg)

#### TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)


### CERTIFICATIONS

IP67			
Def Stan 81-41			

## OTHER

Master Pack	1	
Nameplate	yes	
Military	yes	

#### ACCESSORIES



info@peli.com • www.peli.com

Document created on 06-01-24