



1650EU Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived. These tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **4 strong polyurethane wheels with stainless steel bearings**
- **Watertight, crushproof, and dustproof**
- 2 level Pick N Pluck™ with convoluted lid foam
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors
- Made in Germany



CONFIGURATIONS



1650EU
Standard



1654
With Padded Dividers



1650NF
No Foam



1650WF
With Foam

DIMENSIONS

Interior (L×W×D)	28.41 x 17.40" x 10.64 (72.2 x 44.2 x 27 cm)
Exterior (L×W×D)	31.55 x 20.51" x 12.47 (80.1 x 52.1 x 31.7 cm)
Lid Depth	1.81" (4.6 cm)
Bottom Depth	8.84" (22.5 cm)
Total Depth	10.65" (27.1 cm)
Int Volume	3.04 ft³ (0.086 m³)
Padlock Hole Diameter	5/16" (12.7 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane

Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLOURS

Black

WEIGHT

Weight With Foam	28.06 lbs (12.7 kg)
Weight Empty	24.03 lbs (10.9 kg)
Buoyancy	181.00 lbs (82.1 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)


CERTIFICATIONS

IP67
MIL C-4150J
Def Stan 81-41
ATA 300

OTHER

Wheels	4
Extendable Handle	yes
Master Pack	1
Nameplate	yes
Reduced Area	yes
Military	yes

ACCESSORIES



1651
4 pc. Replacement Foam Set



1653
Replacement O-ring



1655
Padded Divider Set



1659
Photo/Lid Organizer



1650EUTP
TrekPak Case Divider Kit



1507
Quick Mounts - set of 4



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 05-29-24