



# 1505

## Air

The 1505 Air case is a versatile, shallow attaché-style case with built-in functionality to support panel mounting in the lid and base. Protect laptops and sensitive electronics or leverage the out-of-the-box panel mounting capability to engineer your own mobile communications system, cradlepoint, or battery charging station. Whether you're a construction professional transporting your laptop to the site, a law enforcement team relying on a cradlepoint to maintain communications, or prototyping a new medical device, the 1505 Air case delivers the ultimate combination of durability, portability, and versatility.

- Integriertes Blendensystem für die Panelmontage
- Wasserdicht, bruchsicher, staubdicht
- IP67- und MIL-SPEC-zertifiziert
- Superleichtes proprietäres HPX<sup>2</sup>™ Polymer - bis zu 40 % leichter
- Press and Pull™ Verschlüsse
- Automatisches Druckausgleichsventil - gleicht den Innendruck aus, hält Wasser fern
- Klappbarer, spritzbeschichteter Griff
- Wasserdichte O-Ring-Dichtung
- Vorhängeschloss-Verstärkung aus Edelstahl
- Limited Lifetime Warranty



## KONFIGURATIONEN



**1505**  
Standard



**1505NF**  
No Foam



**1505WF**  
With Foam



**1505TP**  
With TrekPak Divider System

## GRÖSSE

|                              |   |
|------------------------------|---|
| <b>INNERE</b>                | 18.29 x 13.26" x 5.46 (46.5 x 33.7 x 13.9 cm) |
| <b>AUSSEN</b>                | 20.22 x 16.38" x 6.10 (51.4 x 41.6 x 15.5 cm) |
| <b>Deckeltiefe</b>           | 1.93" (4.9 cm)                                |
| <b>Bodentiefe</b>            | 3.53" (9 cm)                                  |
| <b>Gesamttiefe</b>           | 5.46" (13.9 cm)                               |
| <b>Innenvolumen</b>          | 0.77 ft <sup>3</sup> (0.022 m <sup>3</sup> )  |
| <b>Padlock Hole Diameter</b> | 5/16" (12.7 cm)                               |

## MATERIALEN

|                        |                                 |
|------------------------|---------------------------------|
| <b>Gehäuse</b>         | Proprietary Polypropylene Blend |
| <b>Verschluss</b>      | ABS                             |
| <b>O-Ring Dichtung</b> | EPDM                            |
| <b>Stifte</b>          | Stainless Steel                 |

|                           |  |
|---------------------------|--|
| <b>Schaumstoff</b>        | Polyurethane                                       |
| <b>Ausgleichsschraube</b> | ABS  |
| <b>Ausgleichsventil</b>   | Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven    |
| <b>Handgriff</b>          | Polypropylene and Thermoplastic Rubber Side Handle |

## FARBEN

---

■ Black

## GEWICHT

---

|                                 |                     |
|---------------------------------|---------------------|
| <b>Gewicht mit Schaumstoff</b>  | 6.55 lbs (3 kg)     |
| <b>Gewicht ohne Schaumstoff</b> | 5.80 lbs (2.6 kg)   |
| <b>Schwimmfähigkeit</b>         | 54.00 lbs (24.5 kg) |

## TEMPERATUR

---

|                        |                 |
|------------------------|-----------------|
| <b>min. Temperatur</b> | 0°F (-17.8 °C)  |
| <b>max. Temperatur</b> | 160°F (71.1 °C) |

## ZUBEHÖR

---



**1505FS**  
3 St. Ersatz-Schaumstoffeinsätze



**1472**  
Shoulder Strap

---

### Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

Document created on 04-05-25