

# 1200 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

#### • Watertight, crushproof, and dustproof

• Automatic pressure equalization valve - balances interior pressure, keeps water out

- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Pick N Pluck<sup>™</sup> with convoluted lid foam
- Peli's legendary lifetime guarantee\*\*
- \* Where applicable by law



# CONFIGURATIONS



**1200** Standard



1200NF No Foam



**1200WF** With Foam

# DIMENSIONS

9.31 x 7.13" x 4.12 (23.6 x 18.1 x 10.5 cm)
10.67 x 9.75" x 4.86 (27.1 x 24.8 x 12.3 cm)
1.18" (3 cm)
2.93" (7.4 cm)
4.11" (10.4 cm)
0.16 ft <sup>3</sup> (0.005 m <sup>3</sup> )

#### MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

## COLOURS



## WEIGHT

Weight With Foam	2.87 lbs (1.3 kg)
Weight Empty	2.65 lbs (1.2 kg)
Buoyancy	12.02 lbs (5.5 kg)
Master Pack Weight	25.00 lbs (11.3 kg)
5	. 5,

## TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)

#### CERTIFICATIONS

IP67	
Def Stan	81-41

#### OTHER

Master Pack	6
Military	yes

### ACCESSORIES



**1201** 3 pc. Replacement Foam Set



**1203** Replacement O-ring



1200PF Special Application Panel Frame



**1507** Quick Mounts - set of 4



**1506TSA** TSA Lock



**1500D** Desiccant Silica Gel

Peli c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 04-12-25