

1550EU Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Peli[™] Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

These tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

• Watertight, crushproof, and dustproof

2 level Pick N Pluck[™] with convoluted lid foam
Automatic pressure equalization valve - balances interior pressure, keeps water out

- Comfortable rubber over-molded handle
- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Stainless steel hardware and padlock protectors
- Made in Germany
- Peli's legendary lifetime guarantee**
- * Where applicable by law



CONFIGURATIONS



1550EU Standard



1554 With Padded Dividers



1550NF No Foam



1550WF With Foam

DIMENSIONS

| Interior (L×W×D) | 18.63 x 14.18" x 7.71 (47.3 x 36 x 19.6 cm) |
|-----------------------|---|
| Exterior (L×W×D) | 20.66 x 17.12" x 8.51 (52.5 x 43.5 x 21.6 cm) |
| Lid Depth | 1.75" (4.4 cm) |
| Bottom Depth | 5.87" (14.9 cm) |
| Total Depth | 7.62" (19.4 cm) |
| Int Volume | 1.18 ft ³ (0.033 m ³) |
| Padlock Hole Diameter | 5/16" (12.7 cm) |

MATERIALS

| Body | Polypropylene |
|--------|---------------------|
| Latch | ABS |
| O-Ring | Polymer |
| Pins | Stainless Steel |
| Foam | 1.3 lb Polyurethane |

Purge BodyABSPurge Vent3 Micron Hydrophobic Non-Woven

COLOURS

| Black | Desert Tan | Orange | OD Green |
|--------|------------|--------|----------|
| Silver | Yellow | | |

WEIGHT

| Weight With Foam | 11.90 lbs (5.4 kg) |
|------------------|---------------------|
| Weight Empty | 10.58 lbs (4.8 kg) |
| Buoyancy | 69.89 lbs (31.7 kg) |

TEMPERATURE

| Minimum Temperature | -40°F (-40 °C) |
|---------------------|-----------------|
| Maximum Temperature | 210°F (98.9 °C) |

CERTIFICATIONS

| IP67 | | | |
|----------------|--|--|--|
| MIL C-4150J | | | |
| Def Stan 81-41 | | | |
| ATA 300 | | | |
| | | | |

OTHER

| Master Pack | 2 |
|-------------|-----|
| Nameplate | yes |
| Military | yes |

ACCESSORIES



1551 4 pc. Replacement Foam Set



1507 Quick Mounts - set of 4



1550PF Special Application Panel Frame



1506TSA TSA Lock



1553 Replacement O-ring



1500D Desiccant Silica Gel



1555 Padded Divider Set



1555EMS EMS Accessory Set (Lid Organizer and Divider Set)



1550EUTP TrekPak Case Divider Kit

Peli c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 <u>info@peli.com</u> • <u>www.peli.com</u>

Document created on 04-12-25