

1720

Protector

Long Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Strong polyurethane wheels with stainless steel bearings
- · Watertight, crushproof, and dustproof
- 3-piece foam set
- Automatic pressure equalization valve balances interior pressure, keeps water out
- · Easy open double-throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Stainless steel hardware and padlock protectors



CONFIGURATIONS







1720NF No Foam



1720WF With Foam

DIMENSIONS

Interior (L×W×D) 42.00 x 13.50" x 5.25 (106.7 x 34.3 x 13.3 cm) Exterior (L×W×D) 44.37 x 16.00" x 6.12 (112.7 x 40.6 x 15.5 cm)

 Lid Depth
 1.75" (4.4 cm)

 Bottom Depth
 3.50" (8.9 cm)

 Total Depth
 5.25" (13.3 cm)

 Int Volume
 1.72 ft³ (0.049 m³)

 Padlock Hole Diameter
 5/16" (12.7 cm)

MATERIALS

Body Polypropylene

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

COLOURS

Black

OD Green

WEIGHT

 Weight With Foam
 18.96 lbs (8.6 kg)

 Weight Empty
 16.76 lbs (7.6 kg)

 Buoyancy
 160.94 lbs (73 kg)

 Master Pack Weight
 21.10 lbs (9.6 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 210°F (98.9 °C)

CERTIFICATIONS

Def Stan 81-41

OTHER

Wheels 2
Master Pack 1
Nameplate yes
Military yes

ACCESSORIES



1721 3 pc. Replacement Foam Set



1723 Replacement O-ring



1506TSA TSA Lock



1500D Desiccant Silica Gel



LGMT-001PProtector Case Roof Mount

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 04-04-25