

1600EU Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Peli[™] Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

These tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

• Watertight, crushproof, and dustproof

2 level Pick N Pluck[™] with convoluted lid foam
Automatic pressure equalization valve - balances interior pressure, keeps water out

- Comfortable rubber over-molded handle
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Stainless steel hardware and padlock protectors
- Made in Germany
 Peli's legendary lifetime guarantee**
- * Where applicable by law



CONFIGURATIONS



1600EU Standard



1604 With Padded Dividers



1600NF No Foam



1600WF With Foam

DIMENSIONS

Interior (L×W×D)	21.51 x 16.54" x 7.95 (54.6 x 42 x 20.2 cm)
Exterior (L×W×D)	24.35 x 19.46" x 8.75 (61.8 x 49.4 x 22.2 cm)
Lid Depth	1.75" (4.4 cm)
Bottom Depth	6.12" (15.5 cm)
Total Depth	7.87" (20 cm)
Int Volume	1.64 ft ³ (0.046 m ³)
Padlock Hole Diameter	5/16" (12.7 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS

Purge Vent

COLOURS



WEIGHT

Weight With Foam	14.11 lbs (6.4 kg)	
Weight Empty	13.00 lbs (5.9 kg)	
Buoyancy	117.00 lbs (53.1 kg)	

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)


CERTIFICATIONS

IP67			
MIL C-4150J			
Def Stan 81-41			
ATA 300			

OTHER

Master Pack	2
Nameplate	yes
Military	yes

ACCESSORIES



1601 4 pc. Replacement Foam Set



1603 Replacement O-ring

1506TSA

TSA Lock



1507 Quick Mounts - set of 4



De



1605 Padded Divider Set



1500D Desiccant Silica Gel



1609 Lid Organizer



1600EUTP TrekPak Case Divider Kit



1605EMS EMS Accessory Set (Lid Organizer and Divider Set)



c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 04-12-25