



## iM2435

### Storm

#### Top Loader Case

The Peli™ Storm Case™ has the same legendary DNA as our Peli Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch.

Guaranteed for life, the Peli Storm case is made in the USA and engineered using the finest components.

- **Watertight, crushproof, and dustproof**
- Retractable extension trolley handle
- Two Press & Pull Latches
- In-line Wheels
- O-ring seal
- Lightweight Strong HPX® Resin
- Two stainless steel padlock protectors



## CONFIGURATIONS



**iM2435**  
Standard



**iM2435-X0000**  
No Foam



**iM2435-X0002**  
With Padded Dividers & Lid Organizer



**iM2435-X0001**  
With Foam

## DIMENSIONS

<b>Interior (LxWxD)</b>	17.50 x 6.50" x 15.50 (44.5 x 16.5 x 39.4 cm)
<b>Exterior (LxWxD)</b>	18.63 x 9.25" x 16.50 (47.3 x 23.5 x 41.9 cm)
<b>Lid Depth</b>	2.00" (5.1 cm)
<b>Bottom Depth</b>	13.50" (34.3 cm)
<b>Total Depth</b>	15.5" (39.4 cm)
<b>Int Volume</b>	1.02 ft <sup>3</sup> (0.029 m <sup>3</sup> )
<b>Padlock Hole Diameter</b>	0.37" (0.9 cm)

## MATERIALS

<b>Body</b>	Injection Molded HPX™ high performance resin
<b>Latch</b>	Valox - Polybutylene Terephthalate (PBT)
<b>Latch (Alt)</b>	Xenoy - Polyester/Polycarbonate blend
<b>O-Ring</b>	EPDM
<b>Pins</b>	Stainless Steel
<b>Pins (Alt)</b>	Aluminum
<b>Foam</b>	1.3/1.35 polyester
<b>Purge Body</b>	Valox - Polybutylene Terephthalate (PBT)
<b>Purge Body (Alt)</b>	Xenoy - Polyester/Polycarbonate blend

**Purge Vent**

Gortex membrane

COLOURS

---

■ Black

WEIGHT

---

<b>Weight With Foam</b>	11.15 lbs (5.1 kg)
<b>Weight Empty</b>	10.00 lbs (4.5 kg)
<b>Buoyancy</b>	56.70 lbs (25.7 kg)

TEMPERATURE

---

<b>Minimum Temperature</b>	-20°F (-28.9 °C)
<b>Maximum Temperature</b>	140°F (60 °C)

CERTIFICATIONS

---

**IP67**OTHER

---

<b>Extendable Handle</b>	yes
<b>Master Pack</b>	1
<b>Military</b>	yes

ACCESSORIES

---



**iM2435-FOAM**  
5 pc. Replacement Foam Set



**iM2435-DIV-LIDORG**  
Divider Set & Lid Organizer



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel

**Peli**

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

Document created on 11-21-24