

# 1560

## **Protector**

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- · Strong polyurethane wheels with stainless steel bearings
- Watertight, crushproof, and dustproof
- 2 level Pick N Pluck<sup>™</sup> with convoluted lid foam
- Automatic pressure equalization valve balances interior pressure, keeps
- Comfortable rubber over-molded top and side handles
- · Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors
- Peli's legendary lifetime guarantee\*\*
- \* Where applicable by law



#### CONFIGURATIONS







1564 With Padded Dividers



1560NF No Foam



**1560TP**With TrekPak Divider System



1560WF With Foam



1560TPL
TrekPak Divider System with Mesh Lid Mesh Lid Organizer

1560PDL
Mesh Lid Organizer

1560PDL
Organizer



#### **DIMENSIONS**

Interior (L×W×D) 19.92 x 14.98" x 9.00 (50.6 x 38 x 22.9 cm) Exterior (L×W×D) 22.07 x 17.92" x 10.42 (56.1 x 45.5 x 26.5 cm)

**Lid Depth** 2.00" (5.1 cm) **Bottom Depth** 7.00" (17.8 cm) **Total Depth** 9" (22.9 cm) Int Volume 1.55 ft3 (0.044 m3) Padlock Hole Diameter 0.31" (0.8 cm)

# **MATERIALS**

Body Polypropylene

Latch ABS **O-Ring** Polymer Pins Stainless Steel **Foam** 1.3 lb Polyurethane

**Purge Body** 

**Purge Vent** 3 Micron Hydrophobic Non-Woven

## **COLOURS**



Desert Tan

Orange

Yellow

## WEIGHT

 Weight With Foam
 20.00 lbs (9.1 kg)

 Weight Empty
 17.00 lbs (7.7 kg)

 Buoyancy
 115.00 lbs (52.2 kg)

 Master Pack Weight
 21.00 lbs (9.5 kg)

## **TEMPERATURE**

Minimum Temperature -40°F (-40 °C)
Maximum Temperature 210°F (98.9 °C)

## **CERTIFICATIONS**

IP67

Def Stan 81-41

## **OTHER**

Wheels 2
Extendable Handle yes
Master Pack 1
Nameplate yes
Military yes

## **ACCESSORIES**



**0343** Replacement O-ring



**1561** 4 pc. Replacement Foam Set



**1565** Padded Divider Set



**1569** Lid Organizer



**1560EUTP** TrekPak Case Divider Kit



**1560TPKIT** TrekPak Case Divider Kit



**1560TPDIV** Extra TrekPak Dividers



**1507** Quick Mounts - set of 4



**1506TSA** TSA Lock



**1500D** Desiccant Silica Gel



**1560MP** EZ-Click™ MOLLE Panel

# Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 04-27-25