

1740 Protector Long Case

From stargazing on the top of Mount Everest to a photoshoot in the forests of the Amazon, the 1740 is your ideal method for protecting a telescope, jack hammer, rifles, chainsaw, tripods and lights, and other long gear. We developed the 1740 for easy one person transport and it's depth and length allow for infinite storage possibilities. Like all Peli cases, standard features include a dustproof and watertight seal and it is backed by our legendary lifetime guarantee of excellence.

Also available from Peli: The 1770 Long Case

• Four extra-deep base-to-lid locking cleats that ensure maximum stacking stability

- Watertight, crushproof, and dustproof
- 6-piece Pick n Pluck foam set
- O-ring seal
- Open cell core, polymer wall construction
- Stainless steel hardware and padlock protectors
- Two Integrated Automatic Pressure Equalization Valves
- Two rugged double-wide handles
- Wide-track polyurethane wheels with ball bearings and nylon hubs
- Peli's legendary lifetime guarantee**
- * Where applicable by law



CONFIGURATIONS



1740 Standard



1740NF No Foam



1740WF With Foam

DIMENSIONS

Interior (L×W×D)	40.98 x 12.92" x 12.13 (104.1 x 32.8 x 30.8 cm)
Exterior (L×W×D)	44.16 x 16.09" x 14.00 (112.2 x 40.9 x 35.6 cm)
Lid Depth	2.56" (6.5 cm)
Bottom Depth	9.57" (24.3 cm)
Total Depth	12.13" (30.8 cm)
Int Volume	3.72 ft ³ (0.105 m ³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel

Purge BodyABSPurge Vent3 Micron Hydrophobic Non-Woven

COLOURS

Black

WEIGHT

Weight With Foam	27.00 lbs (12.2 kg)
Weight Empty	22.00 lbs (10 kg)
Buoyancy	267.00 lbs (121.1 kg)
Master Pack Weight	28.47 lbs (12.9 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)

OTHER

Master Pack	1
Nameplate	yes

ACCESSORIES





1741 6 pc. Replacement Foam Set

1743 Replacement O-ring



1630DC Document Container Accessory

1506TSA TSA Lock

Dief Fi Dief Fi Dief Fi



1500D Desiccant Silica Gel

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 04-27-25