



1550EU Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

These tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Watertight, crushproof, and dustproof**
- 2 level Pick N Pluck™ with convoluted lid foam
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Stainless steel hardware and padlock protectors
- Made in Germany
- Peli's legendary lifetime guarantee**
- * Where applicable by law



CONFIGURATIONS



1550EU
Standard



1554
With Padded Dividers



1550NF
No Foam



1550WF
With Foam

DIMENSIONS

Interior (L×W×D)	18.63 x 14.18" x 7.71 (47.3 x 36 x 19.6 cm)
Exterior (L×W×D)	20.66 x 17.12" x 8.51 (52.5 x 43.5 x 21.6 cm)
Lid Depth	1.75" (4.4 cm)
Bottom Depth	5.87" (14.9 cm)
Total Depth	7.62" (19.4 cm)
Int Volume	1.18 ft ³ (0.033 m ³)
Padlock Hole Diameter	5/16" (12.7 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane

Purge Body
Purge Vent

ABS
3 Micron Hydrophobic Non-Woven

COLOURS

- | | | | |
|--|--|--|---|
|  Black |  Desert Tan |  Orange |  OD Green |
|  Silver |  Yellow | | |

WEIGHT

- | | |
|-------------------------|---------------------|
| Weight With Foam | 11.90 lbs (5.4 kg) |
| Weight Empty | 10.58 lbs (4.8 kg) |
| Buoyancy | 69.89 lbs (31.7 kg) |

TEMPERATURE

- | | |
|----------------------------|-----------------|
| Minimum Temperature | -40°F (-40 °C) |
| Maximum Temperature | 210°F (98.9 °C) |

CERTIFICATIONS

- IP67**
- MIL C-4150J**
- Def Stan 81-41**
- ATA 300**

OTHER

- | | |
|--------------------|-----|
| Master Pack | 2 |
| Nameplate | yes |
| Military | yes |

ACCESSORIES



1551
4 pc. Replacement Foam Set



1550PF
Special Application Panel
Frame



1553
Replacement O-ring



1555
Padded Divider Set



1550EUTP
TrekPak Case Divider Kit



1507
Quick Mounts - set of 4



1506TSA
TSA Lock



1500D
Desiccant Silica Gel



1555EMS
EMS Accessory Set (Lid
Organizer and Divider Set)

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 04-11-25