



9440

NOW TWICE AS BRIGHT

The 9440 now offers three pre-set power levels, battery level indication and comes equipped with a lithium ion rechargeable battery. The 9440 moves fast to light up ravines, confined spaces, riverbanks, anyplace generator lights can't go. Deployed, the mast extends 7 feet (2.1 meters) high, shining light over low obstructions encountered by traditional lantern style lights. With a 125 degree beam spread and up to 5300 lumens, your entire work area will have the light you need for a safe and efficient operation. The 9440 is able to run directly from wall power if needed and can be left on charge indefinitely which makes for an invaluable emergency preparedness tool.

The 9440 is maintenance free, using super tough LED lamp modules and a lithium ion battery for up to 8 hours of continuous light.

Adjustable carrying strap included.

- Built Peli tough
- Convenient shoulder strap
- RoHS and CE Compliant
- Equipped with a lithium ion rechargeable battery
- Mast extends 7 feet (2.1 meters) high when deployed
- Up to 5300 lumens
- Up to 8 hours run time



DIMENSIONS

| | |
|--------------------------------|---|
| Head (LxWxD) | 7.87 x 7.87" x 3.50 (20 x 20 x 8.9 cm) |
| Closed (LxWxD) | 37.40 x 7.87" x 7.87 (95 x 20 x 20 cm) |
| Full (LxWxD) | 85.00 x 35.83" x 35.83 (215.9 x 91 x 91 cm) |
| Light Head Height (max) | 85.00" (215.9 cm) |

MATERIALS

| | |
|-------------|--------------------------|
| Body | Polypropylene |
| Head | Polycarbonate (PC) / ABS |
| Mast | Aluminum |
| Lens | Polycarbonate (PC) |

COLOURS

Black

Yellow

LIGHT SPECS

| | |
|-----------------------|------|
| Lumens (High) | 5300 |
| Lumens (Med) | 2800 |
| Lumens (Low) | 1400 |
| Lamp Heads | 1 |
| Lamp Type | LED |
| Number of LEDs | 12 |
| Beam Spread | 125° |
| IP Rating | 65 |

POWER

| | |
|--------------------------------|-----------------|
| Run Time (High) | 1.50 hrs |
| Run Time (Med) | 4.00 hrs |
| Run Time (Low) | 8.00 hrs |
| Battery Type | Lithium-Ion |
| Rechargeable | yes |
| Battery Lifespan | 500 cycles |
| Charge Time | 3 hrs 45 mins |
| Battery Level Indicator | Level indicator |
| Sockets (Primary) | 1 |
| Volts | 14.4v |

WEIGHT

| | |
|---------------|--------------------|
| Weight | 16.09 lbs (7.3 kg) |
|---------------|--------------------|


SWITCH

| | |
|--------------------|------------------------|
| Switch Type | Silicone Rubber Keypad |
|--------------------|------------------------|

ACCESSORIES



9447
DC Vehicle Charger Cord



9483
Power Supply

Peli
c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 01-29-26