



472-PWC-SCBA

Mobile Medical™

SCBA Double Tank Case

This Peli™ iM2950 case securely transports two SCBA tanks. This watertight & crushproof case features a hinged lid, five Press & Pull™ latches, two double-layered soft grip handle, two padlock-able hasps, a Vortex™ valve and comes with a lifetime guarantee.

- SCBA cylinder case holds two tanks up to 7-inches (17.8cm) in diameter
- Tanks sit in foam cradles and are held in place by adjustable straps



DIMENSIONS

| | |
|-------------------------|--|
| Interior (LxWxD) | 29.00 x 18.00" x 10.50 (73.7 x 45.7 x 26.7 cm) |
| Exterior (LxWxD) | 31.30 x 20.40" x 12.20 (79.5 x 51.8 x 31 cm) |
| Lid Depth | 2.00" (5.1 cm) |
| Bottom Depth | 8.50" (21.6 cm) |
| Total Depth | 10.5" (26.7 cm) |
| Int Volume | 3.17 ft ³ (0.09 m ³) |

MATERIALS

| | |
|-------------------------|--|
| Body | Injection Molded HPX™ high performance resin |
| Latch | Valox - Polybutylene Terephthalate (PBT) |
| Latch (Alt) | Xenoy - Polyester/Polycarbonate blend |
| O-Ring | EPDM |
| Pins | Stainless Steel |
| Foam | Aluminum |
| Purge Body | 1.3/1.35 polyester |
| Purge Body (Alt) | Valox - Polybutylene Terephthalate (PBT) |
| Purge Vent | Xenoy - Polyester/Polycarbonate blend |

COLOURS

| | |
|---------|------------|
| ■ Black | ■ OD Green |
|---------|------------|

TEMPERATURE

| | |
|----------------------------|------------------|
| Minimum Temperature | -20°F (-28.9 °C) |
| Maximum Temperature | 140°F (60 °C) |

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

