



iM2275 Storm

Give your gear extra space. With a deeper lid, the iM2275 is the first case in our Peli™ Storm Case™ line that gives you more vertical space to work with for your equipment. This case gives you the freedom to configure multiple 4K cameras, diagnostic circuit readers, or a drone with accessories.

• Watertight, crushproof, and dustproof

- Two Press & Pull Latches
- Two Padlockable Hasps
- Double-layered, Soft-grip Handle
- Vortex™ Valve
- Powerful Hinges
- Lightweight Strong HPX® Resin



CONFIGURATIONS



iM2275
Standard



iM2275-X0000
No Foam



iM2275-X0006
With TrekPak Divider System



iM2275-X0001
With Foam

DIMENSIONS

| | |
|------------------------------|---|
| Interior (L×W×D) | 14.12 x 13.19" x 9.90 (35.9 x 33.5 x 25.1 cm) |
| Exterior (L×W×D) | 15.25 x 15.50" x 10.22 (38.7 x 39.4 x 26 cm) |
| Lid Depth | 3.20" (8.1 cm) |
| Bottom Depth | 6.30" (16 cm) |
| Total Depth | 9.5" (24.1 cm) |
| Int Volume | 1.07 ft ³ (0.03 m ³) |
| Padlock Hole Diameter | 0.37" (0.9 cm) |

MATERIALS

| | |
|-------------------------|--|
| Body | Injection Molded HPX™ high performance resin |
| Latch | Valox - Polybutylene Terephthalate (PBT) |
| Latch (Alt) | Xenoy - Polyester/Polycarbonate blend |
| O-Ring | EPDM |
| Pins | Stainless Steel |
| Pins (Alt) | Aluminum |
| Foam | 1.3/1.35 polyester |
| Purge Body | Valox - Polybutylene Terephthalate (PBT) |
| Purge Body (Alt) | Xenoy - Polyester/Polycarbonate blend |
| Purge Vent | Gortex membrane |

COLOURS

■ Black

WEIGHT

Weight With Foam 10.25 lbs (4.6 kg)
Weight Empty 8.00 lbs (3.6 kg)
Buoyancy 68.80 lbs (31.2 kg)

TEMPERATURE

Minimum Temperature -20°F (-28.9 °C)
Maximum Temperature 140°F (60 °C)

CERTIFICATIONS

IP67

OTHER

Master Pack 3
Military yes

ACCESSORIES



iM-STRAP-S-VER2
Padded Shoulder Strap



iM-LIDSTAY
Lid Stay



iM2275-FOAM
4 pc. Replacement Foam Set



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999

info@peli.com • www.peli.com

Document created on 11-21-24