



## 2315Z0

The hazard horizon is bright. With ATEX Zone 0 (Category 1) Safety Certification, 115 lumens, 75 meters of spot beam distance and an IPX8 Waterproof rating, the Peli™ 2315Z0 flashlight stretches light across dark, hazardous environments without being a source of ignition.

Engineered with an aluminum core and ABS overmoulded plastic, this flashlight is built for rough handling and can survive hard drops. Plus, the sturdy clip attaches to a work vest for fast access and the tail switch activates raw LED power, even when using heavy-duty work gloves.

### **Peli™ 2315Z0 - SEE THE LIGHT AT THE END OF THE TUNNEL**

- Built Peli tough
- 2 AA Batteries (included)
- ATEX Safety Certified Zone 0 (Cat. 1)
- Integrated Clip
- Full / Momentary Activation Tail Switch
- IPX8 1m waterproof
- Helmet mount (included)



### DIMENSIONS

---

|               |                 |
|---------------|-----------------|
| <b>Length</b> | 6.22" (15.8 cm) |
|---------------|-----------------|

### MATERIALS

|               |     |
|---------------|-----|
| <b>Body</b>   | ABS |
| <b>O-Ring</b> | NBR |
| <b>Lens</b>   | PC  |
| <b>Shroud</b> | ABS |
| <b>Clip</b>   | ABS |

### COLOURS

---

|                        |
|------------------------|
| High Visibility Yellow |
|------------------------|

### LIGHT SPECS

---

|                  |     |
|------------------|-----|
| <b>Lamp Type</b> | LED |
|------------------|-----|

### POWER

---

|                           |          |
|---------------------------|----------|
| <b>Battery Size</b>       | AA       |
| <b>Battery Type</b>       | Alkaline |
| <b>Battery Quantity</b>   | 2        |
| <b>Batteries Included</b> | yes      |
| <b>Volts</b>              | 3.0v     |

### WEIGHT

---

|                                 |                 |
|---------------------------------|-----------------|
| <b>Weight With Batteries</b>    | 4.6 oz (130 gr) |
| <b>Weight Without Batteries</b> | 2.8 oz (79 gr)  |

## SWITCH

---

|                    |                       |
|--------------------|-----------------------|
| <b>Switch Type</b> | Momentary Push Button |
| <b>Light Modes</b> | High                  |

## CERTIFICATIONS

---

**IECEx ia**  
**ATEX Zone 0**

| FL1 STANDARD  | HIGH       |
|---|------------|
|    | 115 LUMENS |
|    | 6h 0mins   |
|   | 75m        |
|  | 1403cd     |
|  | IPX8 (1m)  |

---

**Peli**

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 01-30-26*