



1640

Protector

Transport Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **4 strong polyurethane wheels with stainless steel bearings**
- **Watertight, crushproof, and dustproof**
- 3 level Pick N Pluck™ with convoluted lid foam
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Retractable extension trolley handle
- Stainless steel padlock protectors



CONFIGURATIONS



1640
Standard



1644
With Padded Dividers



1640NF
No Foam



1640WF
With Foam

DIMENSIONS

Interior (LxWxD)	23.70 x 24.00" x 13.90 (60.2 x 61 x 35.3 cm)
Exterior (LxWxD)	27.20 x 27.50" x 16.30 (69.1 x 69.9 x 41.4 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	11.90" (30.2 cm)
Total Depth	13.9" (35.3 cm)
Int Volume	4.58 ft ³ (0.13 m ³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane

Purge Body ABS
Purge Vent 3 Micron Hydrophobic Non-Woven

COLOURS

■ Black

WEIGHT

Weight With Foam 38.00 lbs (17.2 kg)
Weight Empty 34.00 lbs (15.4 kg)
Buoyancy 365.00 lbs (165.6 kg)
Master Pack Weight 50.00 lbs (22.7 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C)
Maximum Temperature 210°F (98.9 °C)

CERTIFICATIONS

IP67
Def Stan 81-41

OTHER

Wheels 4
Extendable Handle yes
Master Pack 1
Nameplate yes
Reduced Area yes

ACCESSORIES



0373
Replacement O-ring



0379
Lid Organizer



1641
5 pc. Replacement Foam Set



1645
Padded Divider Set



1507
Quick Mounts - set of 4



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 09-20-24