

# 1120

## Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

#### · Watertight, crushproof, and dustproof

- Automatic pressure equalization valve balances interior pressure, keeps water out
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Pick N Pluck<sup>™</sup> with convoluted lid foam
- Peli's legendary lifetime guarantee\*\*
- \* Where applicable by law



## **CONFIGURATIONS**







1120NF No Foam



1120WF With Foam

#### **DIMENSIONS**

Interior (L×W×D) 7.29 x 4.78" x 3.33 (18.5 x 12.1 x 8.5 cm) Exterior (L×W×D) 8.41 x 6.76" x 3.87 (21.4 x 17.2 x 9.8 cm)

 Lid Depth
 0.50" (1.3 cm)

 Bottom Depth
 2.56" (6.5 cm)

 Total Depth
 3.06" (7.8 cm)

 Int Volume
 0.07 ft³ (0.002 m³)

 Padlock Hole Diameter
 0.19" (0.5 cm)

## **MATERIALS**

Body Polypropylene
Latch Polypropylene
O-Ring Polymer
Pins Stainless Steel
Foam 1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

## **COLOURS**

Black Orange OD Green Yellow

## WEIGHT

 Weight With Foam
 1.43 lbs (0.6 kg)

 Weight Empty
 1.34 lbs (0.6 kg)

 Master Pack Weight
 10.45 lbs (4.7 kg)

#### **TEMPERATURE**

**Minimum Temperature** -40°F (-40 °C) **Maximum Temperature** 190°F (87.8 °C)

## **CERTIFICATIONS**

IP67

Def Stan 81-41

## **OTHER**

Master Pack6Militaryyes

#### **ACCESSORIES**



**1121** 3 pc. Replacement Foam Set



**1123** Replacement O-ring



**1120PF**Special Application Panel Frame



**1507** Quick Mounts - set of 4



**1506TSA** TSA Lock



**1500D** Desiccant Silica Gel