



1490CC2

Protector

Laptop Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Double safety locking latches with keys**
- **Fits notebook computers up to 17.3" L x 11.0" W x 3.3" D (43.94 x 27.94 x 8.38 cm)**
- **Lid organizer and shoulder strap included (14.0" L x 10.8" W x 1.7" D notebooks will fit within the lid organizer)**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Peli's legendary lifetime guarantee**
- * Where applicable by law



DIMENSIONS

Interior (LxWxD)	17.75 x 11.37" x 4.12 (45.1 x 28.9 x 10.5 cm)
Exterior (LxWxD)	19.87 x 13.93" x 4.68 (50.5 x 35.4 x 11.9 cm)
Lid Depth	1.50" (3.8 cm)
Bottom Depth	2.62" (6.7 cm)
Total Depth	4.12" (10.5 cm)
Int Volume	0.48 ft ³ (0.014 m ³)

MATERIALS

Body	ABS
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLOURS

■ Black

WEIGHT

Weight With Foam	6.50 lbs (2.9 kg)
Weight Empty	5.47 lbs (2.5 kg)
Buoyancy	41.00 lbs (18.6 kg)
Master Pack Weight	27.30 lbs (12.4 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C)
Maximum Temperature 210°F (98.9 °C)

CERTIFICATIONS

Def Stan 81-41

OTHER

Master Pack 4
Nameplate yes
Military yes

ACCESSORIES



1493
Replacement O-ring



1498
Computer Lid Organizer



1472
Shoulder Strap



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 04-15-25