

1460TOOL

Protector

Mobile Tool Chest

Sensitive equipment needs protection, and since 1976 the answer has been the Peli[™] Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

• Also available without tray dividers

- Adjustable and removable tray dividers for easy customization
- \bullet Top lid opens up to 180° for on-the-field anti-roll stability when
- open

• Automatic pressure equalization valve - balances interior pressure, keeps water out

- Comfortable rubber over-molded handles
- Easy open double-throw latches
- O-ring seal for dust and water resistant seal (IP66)
- Open cell core with solid wall design strong, light weight
- Tray sizes: Top tray 17.65" x 8.2" x 2.4" (44.83 x 20.83 x 6.10 cm) and
- bottom tray 17.3" x 8.0" x 2.3" (43.94 x 20.32 x 5.84 cm
- Peli's legendary lifetime guarantee**
- * Where applicable by law



DIMENSIONS

18.54 x 9.92" x 10.92 (47.1 x 25.2 x 27.7 cm)
20.85 x 12.73" x 12.75 (53 x 32.3 x 32.4 cm)
4.91" (12.5 cm)
6.01" (15.3 cm)
10.92" (27.7 cm)
1.16 ft³ (0.033 m³)
5/16" (12.7 cm)

MATERIALS

Body	Polypropylene
Latch	EXL
O-Ring	Polymer
Pins	Stainless Steel
Foam	Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLOURS

Black

WEIGHT

 Weight With Foam
 13.00 lbs (5.9 kg)

 Buoyancy
 82.00 lbs (37.2 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)

CERTIFICATIONS

IP66

OTHER

Nameplate	yes
Military	yes

ACCESSORIES



1463 Replacement O-ring



1506TSA TSA Lock



1500D Desiccant Silica Gel

Peli c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 05-01-24