

5050R

Get local to long distance in a slide. The new Peli™ 5050R flashlight features flood to spot technology: Flood position projects a wide beam to illuminate your work area and spot beam for a long distance focused beam. Get power for the work day and your smartphone. Recharge the 5050R by connecting directly to its Micro USB port. Or connect to a USB port to power your smartphone or any other USB powered device. The 5050R: it's our



- Lithium Ion Rechargeable Battery
- 4 modes: Boost / High / Low / Flashing
- Up to 201m Beam Distance
- Up to 883 Lumens

DIMENSIONS

Length 6.16" (15.6 cm)

MATERIALS

Body Aluminum with Type II Anodized

NBR **O-Ring**

AR Coated Glass Lens

Shroud Aluminum with Type II Anodized

COLOURS

Black

LIGHT SPECS

LED **Lamp Type**

POWER

Battery Size 18650 **Battery Type** Lithium **Battery Quantity** 1 **Batteries Included** yes Rechargeable yes **Charge Time** 6 hrs

Battery Level Indicator Full-time battery indicator

Volts 3.7v

WEIGHT

Weight With Batteries 5.8 oz (164 gr) **Weight Without** 4.1 oz (116 gr) **Batteries**

Switch Type Light Modes Push Button

Boost / High / Low / Flashing

FL1 STANDARD	HIGH	LOW	BOOST
31/4	393 LUMENS	21 LUMENS	883 LUMENS
	2h 30mins	40h 0mins	0h 0mins
	134m	30m	201m
	4488cd	224cd	10093cd
The	IPX8 (1m)		

ACCESSORIES



2389 Replacement Battery