



## V550

### Vault

#### Equipment Case

Built for hard use, high impact and supreme weather resistance, new Vault series gun cases are the most rugged and secure in their class. Equipped with a host of premium protective features at a price more hunters and shooters can afford, as only the 42-year veteran of hard knocks could deliver.

- Four layers of protective foam
- Made in the USA
- Crushproof, dustproof, and weather-resistant
- High-impact polymer assures protection of your firearm, via road, trail or air
- Heavy duty handles are ergonomic and will stand up in even the toughest conditions
- Four push button latches offer secure closure with easy-open access
- Built to safely transport a variety of high-level equipment and gear



## CONFIGURATIONS



**V550**  
Standard



**V550WF**  
With Foam



**V550WD**  
With Padded Dividers



**V550NF**  
No Foam

## DIMENSIONS

<b>Interior (L×W×D)</b>	19.00 x 14.00" x 8.50 (48.3 x 35.6 x 21.6 cm)
<b>Exterior (L×W×D)</b>	22.42 x 17.46" x 9.16 (56.9 x 44.3 x 23.3 cm)
<b>Lid Depth</b>	1.57" (4 cm)
<b>Bottom Depth</b>	6.93" (17.6 cm)
<b>Total Depth</b>	8.5" (21.6 cm)
<b>Int Volume</b>	1.31 ft <sup>3</sup> (0.037 m <sup>3</sup> )
<b>Padlock Hole Diameter</b>	0.46" (1.2 cm)

## MATERIALS

<b>Body</b>	Polyethylene
<b>Latch</b>	ABS
<b>O-Ring</b>	Polymer
<b>Pins</b>	Stainless Steel
<b>Foam</b>	1.12 lbs. ELE (Polyurethane)
<b>Purge Body</b>	ABS
<b>Purge Vent</b>	3 Micron Hydrophobic Non-Woven

COLOURS

---

■ Black

WEIGHT

---

<b>Weight With Foam</b>	10.73 lbs (4.9 kg)
<b>Weight Empty</b>	9.02 lbs (4.1 kg)
<b>Master Pack Weight</b>	12.92 lbs (5.9 kg)

TEMPERATURE

---

<b>Minimum Temperature</b>	0°F (-17.8 °C)
<b>Maximum Temperature</b>	140°F (60 °C)

ACCESSORIES

---



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel

---

**Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 12-13-25*