



1170 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **The hand-held electronics protection solution**
- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Pick N Pluck™ with convoluted lid foam
- Stainless steel hardware



CONFIGURATIONS



1170
Standard



1170NF
No Foam



1170WF
With Foam

DIMENSIONS

| | |
|------------------------------|--|
| Interior (L×W×D) | 10.54 x 6.04" x 3.16 (26.8 x 15.3 x 8 cm) |
| Exterior (L×W×D) | 11.64 x 8.34" x 3.78 (29.6 x 21.2 x 9.6 cm) |
| Lid Depth | 1.08" (2.7 cm) |
| Bottom Depth | 2.08" (5.3 cm) |
| Total Depth | 3.16" (8 cm) |
| Int Volume | 0.12 ft ³ (0.003 m ³) |
| Padlock Hole Diameter | 0.19" (0.5 cm) |

MATERIALS

| | |
|-------------------|--------------------------------|
| Body | Polypropylene |
| Latch | ABS |
| O-Ring | Polymer |
| Pins | Stainless Steel |
| Foam | Polyurethane |
| Purge Body | ABS |
| Purge Vent | 3 Micron Hydrophobic Non-Woven |

COLOURS

| | | | |
|--|--|--|--|
|  Black |  Desert Tan |  Orange |  OD Green |
|  Silver |  Yellow | | |

WEIGHT

| | |
|---------------------------|--------------------|
| Weight With Foam | 2.10 lbs (1 kg) |
| Weight Empty | 1.96 lbs (0.9 kg) |
| Buoyancy | 7.25 lbs (3.3 kg) |
| Master Pack Weight | 12.79 lbs (5.8 kg) |

TEMPERATURE

| | |
|----------------------------|-----------------|
| Minimum Temperature | -40°F (-40 °C) |
| Maximum Temperature | 190°F (87.8 °C) |

CERTIFICATIONS

| |
|-------------|
| IP67 |
|-------------|

OTHER

| | |
|--------------------|---|
| Master Pack | 6 |
|--------------------|---|

ACCESSORIES

| | | | | |
|---|---|---|---|---|
|  |  |  |  |  |
| 1171 3 pc. Replacement Foam Set | 1173 Replacement O-ring | 1507 Quick Mounts - set of 4 | 1506TSA TSA Lock | 1500D Desiccant Silica Gel |

Pelican
23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 12-13-25