



1460 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Also available with EMS Organizer and Dividers
- Personalized nameplate service available
- **Top lid opens up to 180° for on-the-field anti-roll stability when open**
- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handles
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Stainless steel hardware and padlock protectors



CONFIGURATIONS



1460
Standard



1460AALG
With Custom Foam for 9430 / 9435



1460NF
No Foam



1460WF
With Foam

DIMENSIONS

| | |
|------------------------------|---|
| Interior (L×W×D) | 18.54 x 9.92" x 10.92 (47.1 x 25.2 x 27.7 cm) |
| Exterior (L×W×D) | 20.85 x 12.73" x 12.75 (53 x 32.3 x 32.4 cm) |
| Lid Depth | 4.91" (12.5 cm) |
| Bottom Depth | 6.01" (15.3 cm) |
| Total Depth | 10.92" (27.7 cm) |
| Int Volume | 1.16 ft ³ (0.033 m ³) |
| Padlock Hole Diameter | 0.31" (0.8 cm) |

MATERIALS

| | |
|---------------|-----------------|
| Body | Polypropylene |
| Latch | EXL |
| O-Ring | Polymer |
| Pins | Stainless Steel |

| | |
|-------------------|--------------------------------|
| Foam | Polyurethane |
| Purge Body | ABS |
| Purge Vent | 3 Micron Hydrophobic Non-Woven |

COLOURS

■ Black

WEIGHT

| | |
|-------------------------|---------------------|
| Weight With Foam | 12.48 lbs (5.7 kg) |
| Weight Empty | 8.75 lbs (4 kg) |
| Buoyancy | 82.00 lbs (37.2 kg) |

TEMPERATURE

| | |
|----------------------------|-----------------|
| Minimum Temperature | -40°F (-40 °C) |
| Maximum Temperature | 190°F (87.8 °C) |

CERTIFICATIONS

IP67

OTHER

| | |
|-----------------|-----|
| Military | yes |
|-----------------|-----|

ACCESSORIES



1461
6 pc. Replacement Foam Set



1463
Replacement O-ring



1507
Quick Mounts - set of 4



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 12-13-25