



1505

Air

The 1505 Air case is a versatile, shallow attaché-style case with built-in functionality to support panel mounting in the lid and base. Protect laptops and sensitive electronics or leverage the out-of-the-box panel mounting capability to engineer your own mobile communications system, cradlepoint, or battery charging station. Whether you're a construction professional transporting your laptop to the site, a law enforcement team relying on a cradlepoint to maintain communications, or prototyping a new medical device, the 1505 Air case delivers the ultimate combination of durability, portability, and versatility.

- Integrated bezel system for panel mounting
- Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified
- Super-light proprietary HPX²™ Polymer - up to 40% lighter
- Press and Pull™ Latches
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Fold down overmolded handle
- Waterproof O-ring seal
- Stainless steel padlock protectors
- Limited Lifetime Warranty



CONFIGURATIONS



1505
Standard



1505NF
No Foam



1505WF
With Foam



1505TP
With TrekPak Divider System

DIMENSIONS

| | |
|------------------------------|---|
| Interior (LxWxD) | 18.29 x 13.26" x 5.46 (46.5 x 33.7 x 13.9 cm) |
| Exterior (LxWxD) | 20.22 x 16.38" x 6.10 (51.4 x 41.6 x 15.5 cm) |
| Lid Depth | 1.93" (4.9 cm) |
| Bottom Depth | 3.53" (9 cm) |
| Total Depth | 5.46" (13.9 cm) |
| Int Volume | 0.77 ft ³ (0.022 m ³) |
| Padlock Hole Diameter | 5/16" (12.7 cm) |

MATERIALS

| | |
|---------------|---------------------------------|
| Body | Proprietary Polypropylene Blend |
| Latch | ABS |
| O-Ring | EPDM |
| Pins | Stainless Steel |

Foam

Polyurethane

Purge Body

ABS

Pelican

Purge Vent

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

Handle

Polypropylene and Thermoplastic Rubber Side Handle

sales@pelican.com www.pelican.com

Document created on 12-13-25

COLOURS

■ Black

WEIGHT

| | |
|-------------------------|---------------------|
| Weight With Foam | 6.55 lbs (3 kg) |
| Weight Empty | 5.80 lbs (2.6 kg) |
| Buoyancy | 54.00 lbs (24.5 kg) |

TEMPERATURE

| | |
|----------------------------|----------------|
| Minimum Temperature | 0°F (-17.8 °C) |
| Maximum Temperature | 140°F (60 °C) |

ACCESSORIES