

0370

Protector

Cube Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- · Large 2-person fold down handles
- · Watertight, crushproof, and dustproof
- 3 level Pick N Pluck™ with convoluted lid foam
 Automatic pressure equalization valve balances interior pressure, keeps
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Stainless steel hardware and padlock protectors



CONFIGURATIONS



0370 Standard



0374 With Padded Dividers



0370NF No Foam



0370WF With Foam

DIMENSIONS

Interior (L×W×D) 24.00 x 24.00" x 24.00 (61 x 61 x 61 cm) Exterior (L×W×D) 26.50 x 26.50" x 25.25 (67.3 x 67.3 x 64.1 cm)

Lid Depth 5.00" (12.7 cm) **Bottom Depth** 19.00" (48.3 cm) **Total Depth** 24" (61 cm) Int Volume 8 ft3 (0.227 m3) Padlock Hole Diameter 0.31" (0.8 cm)

MATERIALS

Body Polypropylene

Latch ABS **O-Ring** Polymer Pins Stainless Steel Foam 1.3 lb Polyurethane

Purge Body ABS

COLOURS



WEIGHT

 Weight With Foam
 41.00 lbs (18.6 kg)

 Weight Empty
 31.97 lbs (14.5 kg)

 Buoyancy
 465.18 lbs (211 kg)

 Master Pack Weight
 46.78 lbs (21.2 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 190°F (87.8 °C)

CERTIFICATIONS

IP67

Def Stan 81-41

OTHER

Master Pack1NameplateyesReduced AreayesMilitaryyes

ACCESSORIES



0357 Cube Case Mobility Package



8 pc. Replacement Foam Set



0373Replacement O-ring



0375 Padded Divider Set



0379 Lid Organizer



1507 Quick Mounts - set of 4



1506TSA TSA Lock



1500D Desiccant Silica Gel

Document created on 12-13-25