

1550

Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- Watertight, crushproof, and dustproof
- 2 level Pick N Pluck[™] with convoluted lid foam
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Stainless steel hardware and padlock protectors



CONFIGURATIONS



1550 Standard



1550NF No Foam



1550TPWith TrekPak Divider System



1554With Padded Dividers



1550WF With Foam

DIMENSIONS

Interior (L×W×D) 18.63 x 14.18" x 7.72 (47.3 x 36 x 19.6 cm) Exterior (L×W×D) 20.66 x 17.20" x 8.40 (52.5 x 43.7 x 21.3 cm)

 Lid Depth
 1.75" (4.4 cm)

 Bottom Depth
 5.87" (14.9 cm)

 Total Depth
 7.62" (19.4 cm)

 Int Volume
 1.18 ft³ (0.033 m³)

 Padlock Hole Diameter
 0.31" (0.8 cm)

MATERIALS

Body Polypropylene

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLOURS



WEIGHT

 Weight With Foam
 11.90 lbs (5.4 kg)

 Weight Empty
 10.58 lbs (4.8 kg)

 Buoyancy
 69.89 lbs (31.7 kg)

 Master Pack Weight
 28.35 lbs (12.9 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C)
Maximum Temperature 190°F (87.8 °C)

CERTIFICATIONS

IP67 MIL C-4150J Def Stan 81-41 ATA 300

OTHER

Master Pack2NameplateyesMilitaryyes

ACCESSORIES



Document created on 08-02-25