



1620 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- **Strong polyurethane wheels with stainless steel bearings**
- **Watertight, crushproof, and dustproof**
- 4 level Pick N Pluck™ with convoluted lid foam
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors



CONFIGURATIONS



1620
Standard



1624
With Padded Dividers



1620NF
No Foam



1620WF
With Foam

DIMENSIONS

Interior (L×W×D)	21.48 x 16.42" x 12.54 (54.6 x 41.7 x 31.9 cm)
Exterior (L×W×D)	24.76 x 19.57" x 13.90 (62.9 x 49.7 x 35.3 cm)
Lid Depth	2.01" (5.1 cm)
Bottom Depth	10.53" (26.7 cm)
Total Depth	12.54" (31.9 cm)
Int Volume	2.56 ft³ (0.072 m³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane

Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLOURS

 Black	 Desert Tan	 OD Green
---	--	--

WEIGHT

Weight With Foam	24.62 lbs (11.2 kg)
Weight Empty	21.20 lbs (9.6 kg)
Buoyancy	149.91 lbs (68 kg)
Master Pack Weight	26.90 lbs (12.2 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	190°F (87.8 °C)

CERTIFICATIONS

IP67
MIL C-4150J
Def Stan 81-41

OTHER

Wheels	2
Extendable Handle	yes
Master Pack	1
Nameplate	yes
Military	yes

ACCESSORIES



1609
Lid Organizer



1621
6 pc. Replacement Foam Set



1622
Pick N Pluck™ Sections Only
(set of 4)



1623
Replacement O-ring



1625
Padded Divider Set



1507
Quick Mounts - set of 4



1506TSA
TSA Lock



1500D
Desiccant Silica Gel



1610MP
EZ-Click™ MOLLE Panel

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 12-13-25