

1690 Protector Transport Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican[™] Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- 4 strong polyurethane wheels with stainless steel bearings
- Large 2-person fold down handles
- · Watertight, crushproof, and dustproof
- 3 level Pick N Pluck[™] with convoluted lid foam
- Automatic pressure equalization valve balances interior pressure, keeps
- water outEasy open double-throw latches
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Retractable extension trolley handle
- Stainless steel padlock protectors



CONFIGURATIONS



1690 Standard



1694 With Padded Dividers



1690NF No Foam



1690WF With Foam

DIMENSIONS

| Interior (L×W×D) | 30.13 x 25.13" x 15.36 (76.5 x 63.8 x 39 cm) |
|-----------------------|--|
| Exterior (L×W×D) | 33.43 x 28.40" x 17.65 (84.9 x 72.1 x 44.8 cm) |
| Lid Depth | 2.86" (7.3 cm) |
| Bottom Depth | 12.14" (30.8 cm) |
| Total Depth | 15" (38.1 cm) |
| Int Volume | 6.73 ft³ (0.191 m³) |
| Padlock Hole Diameter | 0.31" (0.8 cm) |

MATERIALS

| Body | Polypropylene | |
|--------|-----------------|--|
| Latch | ABS | |
| O-Ring | Polymer | |
| Pins | Stainless Steel | |

| Foam | 1.3 lb Polyurethane |
|------------|--------------------------------|
| Purge Body | ABS |
| Purge Vent | 3 Micron Hydrophobic Non-Woven |

COLOURS

WEIGHT

| Weight With Foam | 43.00 lbs (19.5 kg) |
|--------------------|-----------------------|
| Weight Empty | 34.00 lbs (15.4 kg) |
| Buoyancy | 433.00 lbs (196.4 kg) |
| Master Pack Weight | 52.27 lbs (23.7 kg) |

TEMPERATURE

| Minimum Temperature | -40°F (-40 °C) | |
|---------------------|-----------------|--|
| Maximum Temperature | 190°F (87.8 °C) | |

CERTIFICATIONS

IP67 Def Stan 81-41

OTHER

| Wheels | 4 |
|-------------------|-----|
| Extendable Handle | yes |
| Master Pack | 1 |
| Nameplate | yes |
| Reduced Area | yes |

ACCESSORIES



1691 5 pc. Replacement Foam Set



1506TSA TSA Lock



1692 Pick N Pluck™ Sections Only (set of 3)



1500D Desiccant Silica Gel



1693 Replacement O-ring



1699 Lid Organizer



1507 Quick Mounts - set of 4

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 sales@pelican.com • www.pelican.com

Document created on 08-02-25