



472-PWC-SCBA

Mobil-Medizin

SCBA Double Tank Case

This Peli™ iM2950 case securely transports two SCBA tanks. This watertight & crushproof case features a hinged lid, five Press & Pull™ latches, two double-layered soft grip handle, two padlock-able hasps, a Vortex™ valve and comes with a lifetime guarantee.

- SCBA cylinder case holds two tanks up to 7-inches (17.8cm) in diameter
- Tanks sit in foam cradles and are held in place by adjustable straps



GRÖSSE

| | |
|---------------------|--|
| INNERE | 29.00 x 18.00" x 10.50 (73.7 x 45.7 x 26.7 cm) |
| AUSSEN | 31.30 x 20.40" x 12.20 (79.5 x 51.8 x 31 cm) |
| Deckeltiefe | 2.00" (5.1 cm) |
| Bodentiefe | 8.50" (21.6 cm) |
| Gesamttiefe | 10.5" (26.7 cm) |
| Innenvolumen | 3.17 ft ³ (0.09 m ³) |

MATERIALEN

| | |
|---------------------------------|--|
| Gehäuse | Injection Molded HPX™ high performance resin |
| Verschluss | Valox - Polybutylene Terephthalate (PBT) |
| Verschluss (Alt) | Xenoy - Polyester/Polycarbonate blend |
| O-Ring Dichtung | EPDM |
| Stifte | Stainless Steel |
| Schaumstoff | Aluminum |
| Ausgleichsschraube | 1.3/1.35 polyester |
| Ausgleichsschraube (Alt) | Valox - Polybutylene Terephthalate (PBT) |
| Ausgleichsventil | Xenoy - Polyester/Polycarbonate blend |

FARBEN

| | |
|---------|------------|
| ■ Black | ■ OD Green |
|---------|------------|

TEMPERATUR

| | |
|------------------------|------------------|
| min. Temperatur | -20°F (-28.9 °C) |
| max. Temperatur | 140°F (60 °C) |

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999

info@peli.com • www.peli.com

Document created on 07-17-24