



## 1930Z0

### L1™

Same features as L1™ 1930 LED with static-dissipation materials body. Being certified to ATEX safe for use in high-risk hazardous locations, Zone 0 (Category 1) areas, L1™ 1930Z0 LED is ideal for professionals who work in chemical, pharmaceutical, power, oil and gas, and fire rescue industries.



## DIMENSIONS

---

<b>Length</b>	2.64" (6.7 cm)
---------------	----------------

## MATERIALS

<b>Body</b>	Anti-static Impact Modified PC/PBT
<b>O-Ring</b>	Ethylene Propylene
<b>Lens</b>	Polycarbonate (PC)
<b>Shroud</b>	Anti-static Impact Modified PC/PBT
<b>Contact Spring Retainer</b>	Phosphore Bronze

## COLOURS

---

<span style="background-color: gray; display: inline-block; width: 10px; height: 10px;"></span>	Gray
---	------

## LIGHT SPECS

---

<b>Lamp Type</b>	LED
------------------	-----

## POWER

---

<b>Battery Size</b>	LR 44
<b>Battery Type</b>	Alkaline
<b>Battery Quantity</b>	4
<b>Batteries Included</b>	yes
<b>Volts</b>	6.0v

## WEIGHT

---

<b>Weight With Batteries</b>	0.9 oz (26 gr)
<b>Weight Without Batteries</b>	0.6 oz (17 gr)
<b>Packaged Weight</b>	0.8 oz (23 gr)

## SWITCH

---

<b>Switch Type</b>	Push Button Tail
<b>Light Modes</b>	On / Off

## CERTIFICATIONS


---

### ATEX Zone 0

### OTHER

---

**Minimum Pack** 12  
**Military** yes  
**Package Code** C

FL1 STANDARD	HIGH
	12 LUMENS
	4h 15mins
	17m
	70cd
	IPX4

---

**Peli**

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 01-08-26*