

# 2220Z1 VB3™

The VB3<sup>TM</sup> 2220Z1 LED light has dual super bright white LEDs that may never need replacing and provide over 30 hours of run time. The light is ATEX safe for use in hazardous Zone 1 (Category 2) locations. The VB3<sup>TM</sup> 2220Z1 LED is ideal for professionals who work in areas with high risk of explosion such as chemical, pharmaceutical, power, oil and gas, and fire rescue.



#### DIMENSIONS

Length

# 3.50" (8.9 cm)

## MATERIALS

Body	Anti-static Impact Modified PC/PBT
Clip	Anti-static Impact Modified PC/PBT
<b>Contact Spring Retainer</b>	Stainless Steel

#### COLOURS

Black High Visibility Yellow

#### LIGHT SPECS

|--|--|--|

#### POWER

Battery Size	CR2032	
Battery Type	Lithium	
Battery Quantity	2	
<b>Batteries Included</b>	yes	
Volts	3.0v	

## WEIGHT

Weight With Batteries	1.0 oz (28 gr)
Weight Without Batteries	0.9 oz (26 gr)
Packaged Weight	1.7 oz (48 gr)

## SWITCH

Switch Type

# CERTIFICATIONS

#### ATEX Zone 1

#### OTHER

Minimum Pack	6
Military	yes
Package Code	С

FL1 STANDARD	HIGH	
	8 LUMENS	
	8h 0mins	
	19m	
	92cd	
	IPX4	

Peli c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 08-15-25