

# 1700

# Protector

Long Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Strong polyurethane wheels with stainless steel bearings
- Watertight, crushproof, and dustproof
- 3-piece foam set
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down side handle
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Stainless steel hardware and padlock protectors



#### **CONFIGURATIONS**







**1700NF** No Foam



1700WF With Foam

## **DIMENSIONS**

Interior (L×W×D) 35.75 x 13.50" x 5.25 (90.8 x 34.3 x 13.3 cm) Exterior (L×W×D) 38.12 x 16.00" x 6.12 (96.8 x 40.6 x 15.5 cm)

 Lid Depth
 1.75" (4.4 cm)

 Bottom Depth
 3.50" (8.9 cm)

 Total Depth
 5.25" (13.3 cm)

 Int Volume
 1.47 ft³ (0.042 m³)

 Padlock Hole Diameter
 5/16" (12.7 cm)

### **MATERIALS**

**Body** Polypropylene

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

### **COLOURS**

Black OD Green

### WEIGHT

 Weight With Foam
 16.98 lbs (7.7 kg)

 Weight Empty
 16.09 lbs (7.3 kg)

 Buoyancy
 136.91 lbs (62.1 kg)

 Master Pack Weight
 19.10 lbs (8.7 kg)

#### **TEMPERATURE**

**Minimum Temperature** -40°F (-40 °C) **Maximum Temperature** 190°F (87.8 °C)

# **CERTIFICATIONS**


IP67

MIL C-4150J Def Stan 81-41

## OTHER

Wheels 2
Master Pack 1
Military yes

### **ACCESSORIES**



**1701** 3 pc. Replacement Foam Set



1703 Replacement O-ring



**1506TSA** TSA Lock



**1500D** Desiccant Silica Gel



**LGMT-001P**Protector Case Roof Mount

#### Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com