



1460TOOL

Protector

Mobile Tool Chest

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Also available without tray dividers
- **Adjustable and removable tray dividers for easy customization**
- **Top lid opens up to 180° for on-the-field anti-roll stability when open**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handles
- Easy open double-throw latches
- O-ring seal for dust and water resistant seal (IP66)
- Open cell core with solid wall design - strong, light weight
- Tray sizes: Top tray 17.65" x 8.2" x 2.4" (44.83 x 20.83 x 6.10 cm) and bottom tray 17.3" x 8.0" x 2.3" (43.94 x 20.32 x 5.84 cm)
- Peli's legendary lifetime guarantee**
- * Where applicable by law



DIMENSIONS

Interior (LxWxD)	18.54 x 9.92" x 10.92 (47.1 x 25.2 x 27.7 cm)
Exterior (LxWxD)	20.85 x 12.73" x 12.75 (53 x 32.3 x 32.4 cm)
Lid Depth	4.91" (12.5 cm)
Bottom Depth	6.01" (15.3 cm)
Total Depth	10.92" (27.7 cm)
Int Volume	1.16 ft ³ (0.033 m ³)
Padlock Hole Diameter	5/16" (12.7 cm)

MATERIALS

Body	Polypropylene
Latch	EXL
O-Ring	Polymer
Pins	Stainless Steel
Foam	Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLOURS

■ Black

WEIGHT

Weight With Foam	13.00 lbs (5.9 kg)
Buoyancy	82.00 lbs (37.2 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C)
Maximum Temperature 210°F (98.9 °C)

CERTIFICATIONS

IP66

OTHER

Nameplate yes
Military yes

ACCESSORIES



1463
Replacement O-ring



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 07-17-24