



## 9415Z0

### 9410L + SAFETY = 9415Z0

#### Everything that's great about the 9410L LED Lantern, plus safety certificates

At just 1.4kg (3 pounds) and 530 lumens, the 9415Z0 LED Lantern packs the power without the weight. Four LEDs, powered by the latest generation Ni-MH batteries illuminate a distance of 272 meters. And it's loaded with innovative technology and features you have come to expect from Peli.

Safety certified for the most volatile work areas, the 9415Z0 LED Lantern is safe and one of the most compact, high output lanterns on the market. Certified to ATEX Zone 0 (Category 1)



### DIMENSIONS

|        |                 |
|--------|-----------------|
| Length | 8.75" (22.2 cm) |
|--------|-----------------|

### MATERIALS

|        |                                       |
|--------|---------------------------------------|
| Body   | Anti-static Impact Modified PC/PBT    |
| O-Ring | EPDM                                  |
| Lens   | Anti-static coated Polycarbonate (PC) |
| Shroud | Anti-static Impact Modified PC/PBT    |

### COLOURS

|                                                                                     |                        |
|-------------------------------------------------------------------------------------|------------------------|
|  | High Visibility Yellow |
|-------------------------------------------------------------------------------------|------------------------|

### LIGHT SPECS

|           |     |
|-----------|-----|
| Lamp Type | LED |
|-----------|-----|

### POWER

|                         |         |
|-------------------------|---------|
| Battery Size            | C       |
| Battery Type            | NiMH    |
| Battery Quantity        | 4       |
| Batteries Included      | yes     |
| Rechargeable            | yes     |
| Charge Time             | 15 hrs  |
| Battery Level Indicator | RGB LED |
| Volts                   | 4.8v    |

### WEIGHT

|                       |                   |
|-----------------------|-------------------|
| Weight With Batteries | 58.2 oz (1650 gr) |
|-----------------------|-------------------|

### SWITCH

|             |             |
|-------------|-------------|
| Switch Type | Push Button |
|-------------|-------------|

Light Modes

High / Low / Flashing

CERTIFICATIONS

ATEX Zone 0  
IECEX ia

OTHER

Minimum Pack 1  
Package Code B

| FL1 STANDARD                                                                        | HIGH          | LOW           |
|-------------------------------------------------------------------------------------|---------------|---------------|
|    | 530<br>LUMENS | 202<br>LUMENS |
|    | 4h 30mins     | 11h 30mins    |
|   | 272m          | 166m          |
|  | 18480cd       | 6914cd        |
|  | IPX4          |               |

ACCESSORIES



9416  
Deck/Dash Charger Base Unit



8056F  
12v Plug-in for Fast Charger



941820  
Replacement Battery



6061F  
Direct Wiring Rig for Fast  
Charger



6058H  
220V Transformer (UK)

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 05-12-24*