



AL3620-1710AC

Trusted for over 40 years by the US Military, Single Lid Cases offer 20% more protective material in the edges and corners, where it is needed most, ensuring that valuable equipment is kept safe from any unforeseen elements. Available in several sizes, these cases are completely customizable with a wide range of bolt-on options like document holders, casters, humidity indicators and much more.


- Lignes de partage résistantes aux éclaboussures avec joints à rainure et languette moulés étroitement serrés en permanence, même
- Angles et bords renforcés pour protection additionnelle contre les impacts
- Épaulements et cannelures moulées pour empilement sûr et sans glissement, plus de force colonnaire et protection renforcée
- Matériel encastré pour une protection renforcée
- Verrous anti-tiraillement positif prévenant la séparation du couvercle après impact et réduisant les contraintes sur le matériel
- Inserts métalliques surmoulés brevetés aux points d'attache pour fermeture et charnière pour une meilleure résistance
- Construction monobloc, moulée à partir de polyéthylène léger résistant aux chocs




CONFIGURATIONS




AL3620-1710AC
Standard



AL3620-1710-RP
Empty



AL3620-1710RPC
No Foam, With Casters



AL3620-1710RPFC
With Foam, With Casters

DIMENSIONS

| | |
|-----------------------------|--|
| INTÉRIEUR | 35.87 x 19.87" x 27.27 (91.1 x 50.5 x 69.3 cm) |
| EXTÉRIEUR | 38.87 x 22.87" x 29.46 (98.7 x 58.1 x 74.8 cm) |
| profondeur couvercle | 10.15" (25.8 cm) |
| profondeur fond | 17.12" (43.5 cm) |
| profondeur totale | 27.27" (69.3 cm) |
| volume intérieur | 11.25 ft ³ (0.319 m ³) |

MATÉRIAUX

| | |
|-----------------------|--|
| corps | RotoMolded Polyethylene |
| loquet | Steel (Nickel-black Plated) |
| joint torique | Silicone Sponge |
| mousse | No Foam, empty case standard Optional PE and PU, 1 and 2 lb. options filled and lined |
| corps de purge | Aluminum |
| poignée | Heavy Duty Injection Molded Standard |
| matériel | Yellow Carbon Steel Standard |

COULEURS

■ Gray - 133 Fed Std
26270

POIDS

poids 50.40 lbs (22.9 kg)
flottabilité 895.80 lbs (406.3 kg)
Master Pack Weight 52.40 lbs (23.8 kg)

TEMPÉRATURE

température minimale -20°F (-28.9 °C)
température maximale 140°F (60 °C)

AUTRES

Domaine militaire Oui

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 07-17-24