



2220Z1 VB3™

The VB3™ 2220Z1 LED light has dual super bright white LEDs that may never need replacing and provide over 30 hours of run time. The light is ATEX safe for use in hazardous Zone 1 (Category 2) locations. The VB3™ 2220Z1 LED is ideal for professionals who work in areas with high risk of explosion such as chemical, pharmaceutical, power, oil and gas, and fire rescue.



DIMENSIONS

Length	3.50" (8.9 cm)
---------------	----------------

MATERIALS

Body	Anti-static Impact Modified PC/PBT
Clip	Anti-static Impact Modified PC/PBT
Contact Spring Retainer	Stainless Steel

COLOURS

 Black	 High Visibility Yellow
---	--

LIGHT SPECS

Lamp Type	LED
------------------	-----

POWER

Battery Size	CR2032
Battery Type	Lithium
Battery Quantity	2
Batteries Included	yes
Volts	3.0v

WEIGHT

Weight With Batteries	1.0 oz (28 gr)
Weight Without Batteries	0.9 oz (26 gr)
Packaged Weight	1.7 oz (48 gr)

SWITCH

Switch Type	Head Flip to Activate
--------------------	-----------------------

Light Modes

On / Off

CERTIFICATIONS

ATEX Zone 1

OTHER

Minimum Pack





6

Military

yes

Package Code

C

FL1 STANDARD	HIGH
	8 LUMENS
	8h 0mins
	19m
	92cd

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999

info@peli.com • www.peli.com

Document created on 04-30-26