



# CLASSIC-V-SERIES-5U

## Classic V

5U

- Engineered to provide secure transport for rack mountable electronics
- Available in 3U, 4U, 5U, 7U, and 9U
- Equipment payload weight ranges for 3U - 5U = 80-100 lbs. (36-45 kg) per case
- Equipment payload weight ranges for 7U - 9U = 100-170 lbs. (45-77 kg) per case
- Black case with Anti-Reflective zinc cobalt black (HCB) catch-and-strike hardware
- 2 Lockable Cable Catches per lid to provide security for your equipment
- Black stainless steel handles
- Molded stacking ribs and coupling catches to secure cases when stacked
- Lid hangers for lid storage while in use
- 19" (48 cm) wide, 33" (83 cm) deep fixed square hole frame for universal equipment fit
- Choice of SAE 10-32 or Metric M6 clip nuts
- Sealed gasket and PRV keeps container watertight and eliminates over pressurization
- 4 removable 3.5" (8.9 cm) heavy duty bottom casters
- REACH and RoHS compliant



### DIMENSIONS

<b>Exterior (LxWxD)</b>	45.80 x 27.00" x 16.60 (116.3 x 68.6 x 42.2 cm)
<b>Rack Height</b>	8.75" (22.2 cm)
<b>Rack Depth</b>	33.00" (83.8 cm)
<b>Interior Lid Depth</b>	2.50" (6.4 cm)
<b>Interior Back Lid Depth</b>	5.25" (13.3 cm)

### MATERIALS

<b>Body</b>	RotoMolded Polyethylene
<b>O-Ring</b>	Silicone Sponge
<b>Purge Body</b>	Aluminum
<b>Hardware</b>	Stainless Steel (Black Oxide) / RoHS Nickel Black
<b>Frame</b>	Steel (Clear Coated)

### COLOURS

■ Black

### WEIGHT

<b>Weight</b>	56.00 lbs (25.4 kg)
---------------	---------------------

#### Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999

[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 11-22-24*