

1460TOOL

Protector

Mobile Tool Chest

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- · Also available without tray dividers
- Adjustable and removable tray dividers for easy customization
- Top lid opens up to 180° for on-the-field anti-roll stability when open
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Comfortable rubber over-molded handles
- Easy open double-throw latches
- O-ring seal for dust and water resistant seal (IP66)
- Open cell core with solid wall design strong, light weight
- Tray sizes: Top tray 17.65" x 8.2" x 2.4" (44.83 x 20.83 x 6.10 cm) and bottom tray 17.3" x 8.0" x 2.3" (43.94 x 20.32 x 5.84 cm
- Peli's legendary lifetime guarantee**
- * Where applicable by law



DIMENSIONS

Interior (L×W×D) 18.54 x 9.92" x 10.92 (47.1 x 25.2 x 27.7 cm) Exterior (L×W×D) 20.85 x 12.73" x 12.75 (53 x 32.3 x 32.4 cm)

 Lid Depth
 4.91" (12.5 cm)

 Bottom Depth
 6.01" (15.3 cm)

 Total Depth
 10.92" (27.7 cm)

 Int Volume
 1.16 ft³ (0.033 m³)

 Padlock Hole Diameter
 5/16" (12.7 cm)

MATERIALS

Body Polypropylene

LatchEXLO-RingPolymerPinsStainless SteelFoamPolyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLOURS



WEIGHT

 Weight With Foam
 13.00 lbs (5.9 kg)

 Buoyancy
 82.00 lbs (37.2 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 190°F (87.8 °C)

CERTIFICATIONS

IP66

OTHER

Nameplate yes Military yes

ACCESSORIES



1463 Replacement O-ring



1506TSA TSA Lock



1500D Desiccant Silica Gel

Peli

Document created on 09-16-25