

# 0550

### Protector

Transport Case

With over 11 cubic feet (0.311 cubic meters) of space, you can store, protect, and move large loads in seconds. The reinforced honeycomb deck and lid construction provide support for heavy equipment, or multiple stacking on a 463L pallet. Opening the case at any altitude is not a problem- the dual integrated automatic pressure equalization valves keep moisture out and prevent vacuum lock, and the double wide grip makes lifting easy. With an IP55 certification, the 0550 Transport Case will protect your gear against rain and dirt. The 0550 Transport Case: Built to move-by forklift, by wheel, by hand.

- Built to move: by forklift, by wheel or by hand
- Fit six 0550 Cases per 463L military pallet, 18 when stacked!
- Over 11ft3 (.311m3) of storage space
- Dual Integrated Automatic Pressure Equalization Valves
- Easy open double-throw latches
- Four extra-deep base-to-lid locking cleats ensure maximum stacking stability
- Locking metal Lidstays keep lid locked in open position
- O-ring seal for dust and water resistant seal (IP55)
- Open cell core with solid wall design strong, light weight
- Optional Caster Wheel Kit complete with brakes
- Optional Pallet Riser Kit
- Reinforced honeycomb deck and lid for added strength
- Stainless steel hardware and padlock protectors
- Store documents outside the case with our Document Container
- Peli's legendary lifetime guarantee\*\*
- \* Where applicable by law



### **CONFIGURATIONS**







0550NF No Foam



**0550WF** With Foam

#### **DIMENSIONS**

Interior (L×W×D) 47.57 x 24.07" x 17.68 (120.8 x 61.1 x 44.9 cm) Exterior (L×W×D) 51.05 x 27.54" x 22.79 (129.7 x 70 x 57.9 cm)

 Lid Depth
 3.19" (8.1 cm)

 Bottom Depth
 14.49" (36.8 cm)

 Total Depth
 17.68" (44.9 cm)

 Int Volume
 11.72 ft³ (0.332 m³)

 Padlock Hole Diameter
 0.31" (0.8 cm)

#### **MATERIALS**

**Body** Polypropylene

LatchABSO-RingPolymerPinsStainless Steel

Purge Body ABS

**Purge Vent** 3 Micron Hydrophobic Non-Woven

# **COLOURS**



# WEIGHT

 Weight With Foam
 95.00 lbs (43.1 kg)

 Weight Empty
 79.20 lbs (35.9 kg)

 Buoyancy
 820.00 lbs (371.9 kg)

 Master Pack Weight
 95.00 lbs (43.1 kg)

### **TEMPERATURE**

**Minimum Temperature** -40°F (-40 °C) **Maximum Temperature** 190°F (87.8 °C)

### **CERTIFICATIONS**

Zone 20

### **OTHER**

Master Pack 1

# **ACCESSORIES**



**0507** Caster Wheel Kit



**0508** Pallet Riser Kit



**0551** 6 pc. Replacement Foam Set



**1630DC**Document Container
Accessory



1507 Quick Mounts - set of 4



**1506TSA** TSA Lock



**1500D** Desiccant Silica Gel

#### Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 11-08-25