



## 472-PWC-DW3300

### Mobile Armory™

FieldPak

The FieldPak from Peli-Hardigg™ combines a softshell padded rifle case with our toughest hardshell protective case for the best of both worlds. In the field, the softshell padded case is lightweight and maneuverable enough to get you into position quickly. On the move, the padlockable hardshell case backs it up with impact, temperature, and moisture resistance for total protection. Together, they offer the most security possible for your weapon. Don't go halfway when it comes to protecting your weapon - go double duty.


- Six Press & Pull Latches
- Two Double-layered, Soft-grip Handles
- Two Padlockable Hasps
- In-line Wheels
- Vortex™ Valve
- Powerful Hinges
- Lightweight Strong HPX™ Resin
- Watertight
- Peli's limited lifetime guarantee\*
- \*Where applicable by law




## CONFIGURATIONS




**472-PWC-DW3300**  
Standard




**472-PWC-DW3300-BLK-BLK**  
Black Case With Black Soft Case



**472-PWC-DW3300-BLK-COY**  
Black Case With Coyote Soft Case



**472-PWC-DW3300-OD-BLK**  
Green Case With Black Soft Case



**472-PWC-DW3300-OD-COY**  
Green Case With Coyote Soft Case

## DIMENSIONS

<b>Interior (LxWxD)</b>	50.50 x 14.00" x 6.00 (128.3 x 35.6 x 15.2 cm)
<b>Exterior (LxWxD)</b>	53.80 x 16.50" x 6.70 (136.7 x 41.9 x 17 cm)
<b>Lid Depth</b>	2.00" (5.1 cm)
<b>Bottom Depth</b>	4.00" (10.2 cm)
<b>Total Depth</b>	6" (15.2 cm)
<b>Int Volume</b>	2.45 ft <sup>3</sup> (0.069 m <sup>3</sup> )

## MATERIALS

<b>Body</b>	Injection Molded HPX™ high performance resin
<b>Latch</b>	Valox - Polybutylene Terephthalate (PBT)
<b>Latch (Alt)</b>	Xenoy - Polyester/Polycarbonate blend
<b>O-Ring</b>	Silicone Sponge
<b>Pins</b>	Stainless Steel
<b>Foam</b>	1.3/1.35 polyester
<b>Purge Body</b>	Valox - Polybutylene Terephthalate (PBT)

**Purge Body (Alt)** Xenoy - Polyester/Polycarbonate blend  
**Purge Vent** Gortex membrane

## COLOURS

---

■ Black      ■ OD Green

## WEIGHT

---

**Weight** 23.00 lbs (10.4 kg)

## TEMPERATURE

---

**Minimum Temperature** -20°F (-28.9 °C)  
**Maximum Temperature** 140°F (60 °C)

## OTHER

---

**Wheels** 2

---

### **Peli**

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 07-17-24*