



1610M

Protector

Mobility Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **4" diameter x 1.5" wide (10.2 x 3.8cm) heavy duty polyurethane wheels with stainless steel bearings**
- **Water resistant, crushproof, and dust resistant**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors



CONFIGURATIONS



1610M
Standard



1610MNF
No Foam



1610MWF
With Foam

DIMENSIONS

Interior (LxWxD)	21.78 x 16.69" x 10.62 (55.3 x 42.4 x 27 cm)
Exterior (LxWxD)	26.20 x 23.00" x 13.68 (66.5 x 58.4 x 34.7 cm)
Lid Depth	2.05" (5.2 cm)
Bottom Depth	8.57" (21.8 cm)
Total Depth	10.62" (27 cm)
Int Volume	2.23 ft ³ (0.063 m ³)
Padlock Hole Diameter	5/16" (12.7 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLOURS

■ Black

WEIGHT

Weight With Foam	29.10 lbs (13.2 kg)
Weight Empty	26.30 lbs (11.9 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)

CERTIFICATIONS

IP57

OTHER

Wheels	2
Extendable Handle	yes
Master Pack	1
Nameplate	yes
Military	yes

ACCESSORIES



1609
Lid Organizer



1611
5 pc. Replacement Foam Set



1615
Padded Divider Set



1623
Replacement O-ring



1507
Quick Mounts - set of 4



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 07-17-24