



# 1535

## Air

### Carry-On Case

Peli™ Air cases are the toughest and lightest cases Peli has to offer. Designed with a super-light proprietary HPX<sup>2</sup> polymer construction, each Peli Air case is up to 40 percent lighter than an average polymer case, yet still extremely durable. Peli Air cases are waterproof, crushproof, and dustproof.

The Peli 1535 Air Case provides protection for a wide variety of gear, from camera equipment to camping kits. It is available with foam, without foam, padded dividers, or TrekPak dividers. The Peli 1535 Air Case is the maximum airline carry-on size, so you can travel with your sensitive gear close at hand. This Peli Air case will lighten the load, while protecting your valued possessions.

(Check with your airline for exact measurement requirements)

- Maximum airline carry on size\*
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Fold down over-molded handle
- Retractable extension trolley handle
- Stainless steel padlock protectors
- Business card holder
- Quiet rolling stainless-steel bearing wheels
- \*Check with your airline for exact measurement requirements
- Press and Pull™ Latches
- Limited Lifetime Warranty
- Super-light proprietary HPX<sup>2</sup>™ Polymer - up to 40% lighter
- Waterproof O-ring seal
- Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified



## CONFIGURATIONS



## DIMENSIONS

|                              |   |
|------------------------------|---|
| <b>Interior (L×W×D)</b>      | 20.39 x 11.20" x 7.21 (51.8 x 28.4 x 18.3 cm) |
| <b>Exterior (L×W×D)</b>      | 21.96 x 13.97" x 8.98 (55.8 x 35.5 x 22.8 cm) |
| <b>Lid Depth</b>             | 2.00" (5.1 cm)                                |
| <b>Bottom Depth</b>          | 5.21" (13.2 cm)                               |
| <b>Total Depth</b>           | 7.21" (18.3 cm)                               |
| <b>Int Volume</b>            | 0.95 ft <sup>3</sup> (0.027 m <sup>3</sup> )  |
| <b>Padlock Hole Diameter</b> | 0.31" (0.8 cm)                                |

## MATERIALS

|                   |   |
|-------------------|---|
| <b>Body</b>       | Proprietary Polypropylene Blend                 |
| <b>Latch</b>      | ABS   |
| <b>O-Ring</b>     | EPDM  |
| <b>Purge Body</b> | ABS   |
| <b>Purge Vent</b> | Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven |

## COLOURS

|   |  |   |   |
|---|--|---|---|
|  Black   |  Orange       |  Silver      |  White       |
|  Yellow  |  Graphite     |  Sage / Gray |  French Blue |
|  OCP Tan |  Hunter Green |   |   |

## WEIGHT

|  |                     |
|--|---------------------|
| <b>Weight With Foam</b>                  | 9.98 lbs (4.5 kg)   |
| <b>Weight Empty</b>                      | 8.69 lbs (3.9 kg)   |
| <b>Buoyancy</b>                          | 64.80 lbs (29.4 kg) |
| <b>Weight With TrekPak / Foam Hybrid</b> | 11.91 lbs (5.4 kg)  |

## TEMPERATURE

|                            |                |
|----------------------------|----------------|
| <b>Minimum Temperature</b> | 0°F (-17.8 °C) |
| <b>Maximum Temperature</b> | 140°F (60 °C)  |

## OTHER

|               |   |
|---------------|---|
| <b>Wheels</b> | 2 |
|---------------|---|

## ACCESSORIES

|   |   |   |  |   |
|---|---|---|--|---|
|  |  |  |  |  |
| <b>1535AirFS</b><br>5 pc. Replacement Foam Set                                      | <b>1535AirDS</b><br>Padded Divider Set  | <b>1535TP-KIT</b><br>TrekPak Case Divider Kit                                       | <b>1510TPDIV</b><br>Extra TrekPak Dividers   | <b>1506TSA</b><br>TSA Lock  |
|  |  |  |  |  |
| <b>1500D</b><br>Desiccant Silica Gel  | <b>1535MP</b><br>EZ-Click™ MOLLE Panel  | <b>RucPac-Pro-1</b><br>RucPac Pro Hardcase Backpack Conversion                      | <b>RucPac-normal</b><br>RucPac Standard Hardcase Backpack Conversion                 | <b>1535TPDIV</b><br>Extra TrekPak Dividers  |

[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 09-17-25*