



## 5050R

Get local to long distance in a slide. The new Peli™ 5050R flashlight features flood to spot technology: Flood position projects a wide beam to illuminate your work area and spot beam for a long distance focused beam. Get power for the work day and your smartphone. Recharge the 5050R by connecting directly to its Micro USB port. Or connect to a USB port to power your smartphone or any other USB powered device. The 5050R: it's our rechargeable option that can add some jolt to your text conversations.

- Lithium Ion Rechargeable Battery
- 4 modes: Boost / High / Low / Flashing
- Up to 201m Beam Distance
- Up to 883 Lumens



### DIMENSIONS

<b>Length</b>	6.16" (15.6 cm)
---------------	-----------------

### MATERIALS

<b>Body</b>	Aluminum with Type II Anodized
<b>O-Ring</b>	NBR
<b>Lens</b>	AR Coated Glass
<b>Shroud</b>	Aluminum with Type II Anodized

### COLOURS

 Black
---

### LIGHT SPECS

<b>Lamp Type</b>	LED
------------------	-----

### POWER






<b>Battery Size</b>	18650
<b>Battery Type</b>	Lithium
<b>Battery Quantity</b>	1
<b>Batteries Included</b>	yes
<b>Rechargeable</b>	yes
<b>Charge Time</b>	6 hrs
<b>Battery Level Indicator</b>	Full-time battery indicator
<b>Volts</b>	3.7v

### WEIGHT

<b>Weight With Batteries</b>	5.8 oz (164 gr)
<b>Weight Without Batteries</b>	4.1 oz (116 gr)

SWITCH

Switch Type	Push Button
Light Modes	Boost / High / Low / Flashing

FL1 STANDARD	HIGH	LOW	BOOST
	393 LUMENS	21 LUMENS	883 LUMENS
	2h 30mins	40h 0mins	0h 0mins
	134m	30m	201m
	4488cd	224cd	10093cd
	IPX8 (1m)		

ACCESSORIES



**2389**  
Replacement Battery