

0500 Protector Transport Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli[™] Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Can be inverted and used as a pallet with an airtight cover
- Fit two 0500 Cases per pallet, four when stacked!
- Watertight, crushproof, and dustproof
- · Double wide grip fold down handles makes lifting easy
- Dual Integrated Automatic Pressure Equalization Valves
- Easy open double-throw latches
- Lid is completely removable
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Optional Caster Wheel Kit complete with brakes
- Optional Pallet Riser Kit
- Store documents outside the case with our Document Container
- Peli's legendary lifetime guarantee**
- * Where applicable by law

CONFIGURATIONS



0500 Standard



0500NF No Foam



0500WF With Foam

DIMENSIONS

34.95 x 18.45" x 25.25 (88.8 x 46.9 x 64.1 cm)
39.95 x 23.45" x 28.65 (101.5 x 59.6 x 72.8 cm)
2.25" (5.7 cm)
23.00" (58.4 cm)
25.25" (64.1 cm)
9.42 ft³ (0.267 m³)
0.31" (0.8 cm)

MATERIALS

Body	Polypropylene
Latch	EXL
O-Ring	Polymer

Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLOURS

Black

WEIGHT

Weight With Foam	58.60 lbs (26.6 kg)
Weight Empty	50.00 lbs (22.7 kg)
Buoyancy	780.00 lbs (353.8 kg)
Master Pack Weight	69.00 lbs (31.3 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	190°F (87.8 °C)

1

OTHER

Master Pack

ACCESSORIES



0501 7 pc. Replacement Foam Set

Diel F

1506TSA TSA Lock



0507 Caster Wheel Kit



1500D Desiccant Silica Gel



0508 Pallet Riser Kit



1630DC Document Container Accessory



1507 Quick Mounts - set of 4

Peli c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 08-08-25