



## 1400EU Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

These tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Pick N Pluck™ with convoluted lid foam
- Stainless steel padlock protectors
- Made in Germany



### CONFIGURATIONS



**1400EU**  
Standard



**1400WF**  
With Foam

### DIMENSIONS

|                              |   |
|------------------------------|---|
| <b>Interior (LxWxD)</b>      | 11.87 x 8.97" x 5.15 (30.1 x 22.8 x 13.1 cm)  |
| <b>Exterior (LxWxD)</b>      | 13.68 x 11.61" x 5.75 (34.7 x 29.5 x 14.6 cm) |
| <b>Lid Depth</b>             | 1.18" (3 cm)                                  |
| <b>Bottom Depth</b>          | 4.00" (10.2 cm)                               |
| <b>Total Depth</b>           | 5.18" (13.2 cm)                               |
| <b>Int Volume</b>            | 0.32 ft <sup>3</sup> (0.009 m <sup>3</sup> )  |
| <b>Padlock Hole Diameter</b> | 5/16" (12.7 cm)                               |

### MATERIALS

|                   |                                |
|-------------------|--------------------------------|
| <b>Body</b>       | Polypropylene                  |
| <b>Latch</b>      | ABS                            |
| <b>O-Ring</b>     | Polymer                        |
| <b>Pins</b>       | Stainless Steel                |
| <b>Foam</b>       | 1.3 lb Polyurethane            |
| <b>Purge Body</b> | ABS                            |
| <b>Purge Vent</b> | 3 Micron Hydrophobic Non-Woven |

## COLOURS

---




Black

Silver




Desert Tan

Yellow



Orange



OD Green

## WEIGHT

---

|                         |                    |
|-------------------------|--------------------|
| <b>Weight With Foam</b> | 4.41 lbs (2 kg)    |
| <b>Weight Empty</b>     | 3.97 lbs (1.8 kg)  |
| <b>Buoyancy</b>         | 20.06 lbs (9.1 kg) |

## TEMPERATURE

---

|                            |                 |
|----------------------------|-----------------|
| <b>Minimum Temperature</b> | -40°F (-40 °C)  |
| <b>Maximum Temperature</b> | 210°F (98.9 °C) |

## CERTIFICATIONS

---

**IP67**  
**MIL C-4150J**  
**Def Stan 81-41**

## OTHER

---

|                    |     |
|--------------------|-----|
| <b>Master Pack</b> | 4   |
| <b>Nameplate</b>   | yes |
| <b>Military</b>    | yes |

## ACCESSORIES

---



**1401**

3 pc. Replacement Foam Set



**1403**

Replacement O-ring



**1400PF**

Special Application Panel  
Frame



**1506TSA**

TSA Lock



**1500D**

Desiccant Silica Gel

### Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

Document created on 11-24-24