

# 1650EU Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Peli<sup>TM</sup> Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

These tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

#### • 4 strong polyurethane wheels with stainless steel bearings

- Watertight, crushproof, and dustproof
- 2 level Pick N Pluck<sup>™</sup> with convoluted lid foam
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors
- Made in Germany



## CONFIGURATIONS



1650EU Standard



1654 With Padded Dividers



**1650NF** No Foam



1650WF With Foam

#### DIMENSIONS

| Interior (L×W×D)      | 28.41 x 17.40" x 10.64 (72.2 x 44.2 x 27 cm)   |
|-----------------------|--|
| Exterior (L×W×D)      | 31.55 x 20.51" x 12.47 (80.1 x 52.1 x 31.7 cm) |
| Lid Depth             | 1.81" (4.6 cm)                                 |
| Bottom Depth          | 8.84" (22.5 cm)                                |
| Total Depth           | 10.65" (27.1 cm)                               |
| Int Volume            | 3.04 ft <sup>3</sup> (0.086 m <sup>3</sup> )   |
| Padlock Hole Diameter | 5/16" (12.7 cm)                                |

#### MATERIALS

| Body   | Polypropylene       |
|--------|---------------------|
| Latch  | ABS                 |
| O-Ring | Polymer             |
| Pins   | Stainless Steel     |
| Foam   | 1.3 lb Polyurethane |

Purge BodyABSPurge Vent3 Micron Hydrophobic Non-Woven

## COLOURS

Black

## WEIGHT

| Weight With Foam | 28.06 lbs (12.7 kg)  |
|------------------|----------------------|
| Weight Empty     | 24.03 lbs (10.9 kg)  |
| Buoyancy         | 181.00 lbs (82.1 kg) |

## TEMPERATURE

| Minimum Temperature | -40°F (-40 °C)  |
|---------------------|-----------------|
| Maximum Temperature | 210°F (98.9 °C) |

#### CERTIFICATIONS

IP67 MIL C-4150J Def Stan 81-41 ATA 300

## OTHER

| Wheels            | 4   |
|-------------------|-----|
| Extendable Handle | yes |
| Master Pack       | 1   |
| Nameplate         | yes |
| Reduced Area      | yes |
| Military          | yes |

## ACCESSORIES



**1651** 4 pc. Replacement Foam Set



1507 Quick Mounts - set of 4



1653 Replacement O-ring



1506TSA

TSA Lock



1655 Padded Divider Set



1500D Desiccant Silica Gel



1659 Photo/Lid Organizer



**1650EUTP** TrekPak Case Divider Kit

#### Peli c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 04-27-24