

# 9440

#### **NOW TWICE AS BRIGHT**

The 9440 now offers three pre-set power levels, battery level indication and comes equipped with a lithium ion rechargeable battery. The 9440 moves fast to light up ravines, confined spaces, riverbanks, anyplace generator lights can't go. Deployed, the mast extends 7 feet (2.1 meters) high, shining light over low obstructions encountered by traditional lantern style lights. With a 125 degree beam spread and up to 5300 lumens, your entire work area will have the light you need for a safe and efficient operation. The 9440 is able to run directly from wall power if needed and can be left on charge indefinitely which makes for an invaluable emergency preparedness tool.

The 9440 is maintenance free, using super tough LED lamp modules and a lithium ion battery for up to 8 hours of continuous light.

Adjustable carrying strap included.

- · Built Peli tough
- Convenient shoulder strap
- RoHS and CE Compliant
- Equipped with a lithium ion rechargeable battery
- Mast extends 7 feet (2.1 meters) high when deployed
- Up to 5300 lumens
- Up to 8 hours run time



#### **DIMENSIONS**

Head (L×W×D)	7.87 x 7.87" x 3.50 (20 x 20 x 8.9 cm)
Closed (L×W×D)	37.40 x 7.87" x 7.87 (95 x 20 x 20 cm)
Full (L×W×D)	85.00 x 35.83" x 35.83 (215.9 x 91 x 91 cm)

**Light Head Height** 

(max)

85.00" (215.9 cm)

#### **MATERIALS**

Body	Polypropylene
Head	Polycarbonate (PC) / ABS

Mast Aluminum

**Lens** Polycarbonate (PC)

### **COLOURS**

Black Yellow

### LIGHT SPECS

Lumens (High)	5300
Lumens (Med)	2800
Lumens (Low)	1400
Lamp Heads	1
Lamp Type	LED
Number of LEDs	12
Beam Spread	125°
IP Rating	65

# **POWER**

Run Time (High)1.50 hrsRun Time (Med)4.00 hrsRun Time (Low)8.00 hrsBattery TypeLithium-lonRechargeableyes

Battery Lifespan500 cyclesCharge Time3 hrs 45 minsBattery Level IndicatorLevel indicator

# WEIGHT

**Weight** 16.09 lbs (7.3 kg)

## **SWITCH**

**Switch Type** Silicone Rubber Keypad

# **ACCESSORIES**







**9483** Power Supply

### Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 08-29-25