



# SMAC2128-02/29/05W

## SuperMAC™ 14U

Peli™ SuperMAC™ rackmount cases are ideal for field-deployed equipment and sheltered applications. Typical uses include control consoles and panels, radar and microwave antennas, solid-state circuit electronics, or radio, TV and communications equipment.

- A space-saving, lightweight case with a removable rack option
- Protection for equipment from 20-200 lbs
- Equipment typically will have 40-70 G fragility
- Available in either threaded aluminum frame or a square hole frame up to 14U and 340 lbs



### DIMENSIONS

|                                |  |
|--------------------------------|--|
| <b>Exterior (LxWxD)</b>        | 38.50 x 23.80" x 30.60 (97.8 x 60.5 x 77.7 cm) |
| <b>Rack Depth</b>              | 24.00" (61 cm)                                 |
| <b>Interior Lid Depth</b>      | 2.20" (5.6 cm)                                 |
| <b>Interior Back Lid Depth</b> | 5.20" (13.2 cm)                                |

### MATERIALS

### COLOURS

|                                 |                                     |                                |                                |
|---------------------------------|-------------------------------------|--------------------------------|--------------------------------|
| ■ Black - 032 Fed Std<br>27040  | ■ Olive Drab - 137 Fed<br>Std 34096 | ■ Tan - 250 Fed Std<br>20372   | ■ Red - 130 Fed Std<br>21105   |
| ■ Blue - 135 Pantone<br>292U    | ■ White - 132 Fed Std<br>27925      | ■ Yellow - 136 Pantone<br>012U | ■ Green - 138 Fed Std<br>24052 |
| ■ Orange - 134 Fed Std<br>12197 | ■ Yellow - 131 Fed Std<br>23538     | ■ Maroon - 197 Pantone<br>202U | ■ Blue - 101 Fed Std<br>25052  |
| ■ Purple - 129 Pantone<br>245U  |                                     |                                |                                |

### WEIGHT

|               |                      |
|---------------|----------------------|
| <b>Weight</b> | 74.00 lbs (33.57 kg) |
|---------------|----------------------|

#### Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

Document created on 06-16-26