# iM2500

## Storm

Carry-On Case

The Peli™ Storm Case™ has the same legendary DNA as our Peli Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch.
Guaranteed for life, the Peli Storm case is made in the USA and engineered using the finest components.
The Peli™ iM2500 Storm Case is designed to meet the maximum airline carry-on size, allowing you to keep your sensitive gear securely by your side while traveling. Be sure to verify the specific size requirements with your airline, as they may vary.

- **Watertight, crushproof, and dustproof**
- Two Press & Pull Latches
- Two Padlockable Hasps
- Double-layered, Soft-grip Handle
- Vortex™ Valve
- Powerful Hinges
- Lightweight Strong HPX® Resin
- Check the size allowance of your airline

## CONFIGURATIONS

**iM2500**
Standard

**iM2500-X0000**
No Foam

**iM2500-X0002**
With Padded Dividers

**iM2500-X0006**
With TrekPak Divider System

**iM2500-X0001**
With Foam

## DIMENSIONS

| | |
|---|---|
| **Interior (L×W×D)** | 20.50 x 11.50" x 7.20 (52.1 x 29.2 x 18.3 cm) |
| **Exterior (L×W×D)** | 21.70 x 14.10" x 8.90 (55.1 x 35.8 x 22.6 cm) |
| **Lid Depth** | 2.00" (5.1 cm) |
| **Bottom Depth** | 5.20" (13.2 cm) |
| **Total Depth** | 7.2" (18.3 cm) |
| **Int Volume** | 0.98 $ft^3$ (0.028 $m^3$) |
| **Padlock Hole Diameter** | 0.28" (0.7 cm) |

## MATERIALS

| | |
|---|---|
| **Body** | Injection Molded HPX™ high performance resin |
| **Latch** | Valox - Polybutylene Terephthalate (PBT) |
| **Latch (Alt)** | Xenoy - Polyester/Polycarbonate blend |
| **O-Ring** | EPDM |
| **Pins** | Stainless Steel |
| **Pins (Alt)** | Aluminum |
| **Foam** | 1.3/1.35 polyester |

| | |
|---|---|
| **Purge Body** | Valox - Polybutylene Terephthalate (PBT) |
| **Purge Body (Alt)** | Xenoy - Polyester/Polycarbonate blend |
| **Purge Vent** | Gortex membrane |

## COLOURS

Black | OD Green | Yellow

## WEIGHT

| | |
|---|---|
| **Weight With Foam** | 13.70 lbs (6.21 kg) |
| **Weight Empty** | 11.10 lbs (5.03 kg) |
| **Buoyancy** | 62.56 lbs (28.38 kg) |
| **Master Pack Weight** | 42.10 lbs (19.1 kg) |

## TEMPERATURE

| | |
|---|---|
| **Minimum Temperature** | -20°F (-28.9 °C) |
| **Maximum Temperature** | 140°F (60 °C) |

## CERTIFICATIONS

**IP67**

## OTHER

| | |
|---|---|
| **Extendable Handle** | yes |
| **Master Pack** | 3 |
| **Military** | yes |

## ACCESSORIES

**iM2500-UTILITYORG**
Utility Organizer



**iM2500-FOAM**
5 pc. Replacement Foam Set

**iM2500-DIV**
Padded Divider Set

**iM-STRAP-S-VER2**
Padded Shoulder Strap

**iM-LIDSTAY**
Lid Stay



**iM2500-M4-BEZEL-L**
Lid Bezel Kit (Metric)



**iM2500-MBEZ-B**
Base Bezel Kit (Metric)



**iM2500-TREK**
TrekPak Case Divider Kit

**1555TPDIV**
Extra TrekPak Dividers

**1506TSA**
TSA Lock

**1500D**
Desiccant Silica Gel

**IM2720TPDIV**
Extra TrekPak Dividers

---

**Peli**
c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

*Document created on 10-25-26*