



2410Z0 StealthLite™

Same features as the StealthLite™ 2400 but with the LED module that produces a true, bright collimated LED beam. The StealthLite™ 2410Z0 LED Zone 0 is corrosion proof, resistant to extreme temperatures, and submersible. It is powered by 4 AA alkaline cells and certified to ATEX Zone 20.



DIMENSIONS

| | |
|---------------|-----------------|
| Length | 7.00" (17.8 cm) |
|---------------|-----------------|

MATERIALS

| | |
|--------------------------------|------------------------------------|
| Body | Anti-static Impact Modified PC/PBT |
| O-Ring | Ethylene Propylene |
| Lens | Anti-static PMMA |
| Shroud | Anti-static Impact Modified PC/PBT |
| Contact Spring Retainer | Stainless Steel / Phosphore Bronze |

COLOURS

| |
|------------------------|
| High Visibility Yellow |
|------------------------|

LIGHT SPECS

| | |
|------------------|-----|
| Lamp Type | LED |
|------------------|-----|

POWER

| | |
|-------------------------|----------|
| Battery Size | AA |
| Battery Type | Alkaline |
| Battery Quantity | 4 |
| Volts | 6.0v |

WEIGHT

| | |
|---------------------------------|-----------------|
| Weight With Batteries | 7.3 oz (207 gr) |
| Weight Without Batteries | 3.7 oz (105 gr) |
| Packaged Weight | 8.4 oz (238 gr) |

SWITCH

| | |
|--------------------|--------------------------|
| Switch Type | One-handed Safety Switch |
| Light Modes | On / Off |

CERTIFICATIONS

Peli

ATEX Zone 0

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

OTHER

Document created on 01-29-26

Minimum Pack

6

Package Code

B

| FL1 STANDARD | HIGH |
|---|------------|
|  | 153 LUMENS |
|  | 5h 45mins |
|  | 165m |
|  | 6837cd |
|  | IPX7 |

ACCESSORIES